

CODE NO.	ITEM
1-20398-28	Canon FTb w/lens FD 50mm f/1.8 S.C.
1-20398-29	Canon FTb w/lens FD 50mm f/1.8 S.C. in case
1-20398-26	Canon FTb w/lens FD 50mm f/1.4 S.S.C.
1-20398-27	Canon FTb w/lens FD 50mm f/1.4 S.S.C. in case
1-20398-24	Canon FTb w/lens FD 55mm f/1.2 S.S.C.
1-20398-25	Canon FTb w/lens FD 55mm f/1.2 S.S.C. in case
1-20398-21	Canon FTb body only

# Canon FTb

1-20399-28	Canon FTb black w/lens FD 50mm f/1.8 S.C.
1-20399-29	Canon FTb black w/lens FD 50mm f/1.8 S.C. in case
1-20399-26	Canon FTb black w/lens FD 50mm f/1.4 S.S.C.
1-20399-27	Canon FTb black w/lens FD 50mm f/1.4 S.S.C. in case
1-20399-24	Canon FTb black w/lens FD 55mm f/1.2 S.S.C.
1-20399-25	Canon FTb black w/lens FD 55mm f/1.2 S.S.C. in case
1-20399-21	Canon FTb black body only

## True Versatility, Solid Dependability



**DISCONTINUED PRODUCT**  
Please retain this section for reference purposes.

### SPECIFICATIONS

- **Type:** 35mm single-lens reflex camera with focal plane shutter
- **Picture Size:** 24x36mm
- **Standard Lenses:** Canon FD 55mm f/1.2 S.S.C.; FD 50mm f/1.4 S.S.C.; FD 50mm f/1.8 S.C.
- **Interchangeable Lenses:** FD series for full aperture metering, FL series and R series for stopped down metering
- **Viewfinder:** eye-level pentaprism; Angle Finders A2 and B, Magnifier S, Dioptic Adjustment lenses (-1.2 standard, +1.5, 0, -2.5 and -4 available) for eyesight correction can be attached.
- **Focusing Screen:** central microprism in matte-fresnel field with fine ground glass collar; beam-splitting condenser for meter operation
- **Field-of-View:** 94% vertical, 94% horizontal of picture area; 0.85x magnification with standard 50mm lens at infinity
- **Finder Information:** meter needle and aperture needle, shutter speed indicator, red signal appears when shutter speed is below coupling range of meter, stopped-down metering index mark and battery check mark; under and overexposure warning mark
- **Mirror:** shockless instant-return type; mirror can be fixed in upward position. Aperture is manually operated when mirror is in up position
- **Lens Mount:** Canon breech-lock, FD, FL and R series lenses mountable
- **Lens Functioning:** FD lenses: full aperture metering coupled with automatic diaphragm; FL lenses: stopped-down metering, coupled with automatic diaphragm; R lenses: stopped-down metering with manually-operated diaphragm
- **Shutter:** focal-plane shutter with speeds from 1 to 1/1,000 sec. and B; X synchronization at 1/60 sec.; Shutter button can be locked.
- **Self-Timer:** built-in, activated with shutter button. Approximately 10 sec. time lag. Self-timer lever is also used as stopped-down metering lever and depth-of-field checking lever.
- **Film Speed Range:** ASA 25-2,000
- **Exposure Meter:** built-in, using CdS photocell. Coupled to ASA setting, shutter speed and aperture. Match-needle type full aperture metering mechanism. Central Area Metering System measures center 12% of picture area.
- **Power Source:** one 1.3V mercury battery (Mallory PX625 or Eveready EPX625); battery checker built-in
- **Exposure Meter Coupling Range:** with ASA 100 film, EV2.5 (f/1.2, 1/4 sec.) to EV18 (f/16, 1/1,000 sec.)
- **Ultra-Low Illumination Metering:** Metering possible for ASA 100 film between EV10 (f/22, 1/2 sec.) and EV-3.5 (f/1.2, 15 sec.) with use of optional FTb Booster accessory
- **Flash Synchronization:** FP and X synchronization, automatic time-lag adjusting type; synch. terminal on front of body with cover to prevent electric shock; two exclusive direct contacts on flash shoe
- **Synchronizing Range:** FP class: 1/1,000-1/125 sec.; Speedlite: 1/60 sec. or under; M, MF class: 1/30 sec. or under
- **Canon Auto Tuning (CAT) System:** aperture control by recharging power level signal and distance signal; proper aperture obtained by match-needle system through connection of Canon Speedlite 133D, Auto Ring A<sub>2</sub> or B<sub>2</sub>; CAT used with these lenses: FD 50mm f/1.4 S.S.C., FD 50mm f/1.8 S.C., FD 35mm f/2 S.S.C. and FD 35mm f/3.5 S.C.
- **Film Loading:** QL mechanism is designed for quick loading of any standard 35mm film in cassettes.
- **Winding Lever:** single-stroke operation, 174°; ratchet winding possible
- **Film Rewinding:** performed by rewind crank and button.
- **Frame Counter:** self-resetting type, activated by opening back cover
- **Size:** 144x93x43mm (5<sup>11</sup>/<sub>16</sub>"x3<sup>11</sup>/<sub>16</sub>"x1<sup>11</sup>/<sub>16</sub>"') body only  
144x93x90mm (5<sup>11</sup>/<sub>16</sub>"x3<sup>11</sup>/<sub>16</sub>"x3<sup>9</sup>/<sub>16</sub>"') body with FD 50mm f/1.4 lens
- **Weight:** 750g (1 lb. 10½ oz.) body only; 1055g (2 lbs. 5 oz.) with FD 50mm f/1.4 lens.

Subject to change without notice.

SG1-G1



# ACCESSORIES

## VIEWFINDERS AND ACCESSORIES

CODE NO.	DESCRIPTION
5-40701-22	Magnifier S
5-41041-00	Magnifier Adaptor S
5-40712-00	Angle Finder A-2
5-40711-00	Angle Finder B
5-59212-00	Eye Cup 4S

## DIOPTRIC ADJUSTMENT LENSES

5-05072-00	Dioptric Adjustment Lens S (+3)
5-05073-00	Dioptric Adjustment Lens S (+2)
5-05051-00	Dioptric Adjustment Lens S (+1.5)
5-05075-00	Dioptric Adjustment Lens S (+1)
5-05076-00	Dioptric Adjustment Lens S (+0.5)
5-05041-00	Dioptric Adjustment Lens S (0)
5-05078-00	Dioptric Adjustment Lens S (-0.5)
5-05079-00	Dioptric Adjustment Lens S (-2)
5-05081-00	Dioptric Adjustment Lens S (-3)
5-05082-00	Dioptric Adjustment Lens S (-4)

## BOOSTER

5-60081-00	Booster in Case for Canon FTb
------------	-------------------------------

## FLASH ACCESSORIES

5-00271-31	Speedlite 133D w/Flash Auto Ring A2 (for 50mm f1.8, 35mm f3.5, 35mm f2.0)
5-00271-32	Speedlite 133D w/Flash Auto Ring B2 (for 50mm f1.4, 35mm f3.5, 35mm f2.0)
5-02124-00	Flash Auto Ring A2
5-02125-00	Flash Auto Ring B2

## GADGET BAGS

4-80024-00	Gadget Bag 4
4-80025-00	Gadget Bag G-1

## MISCELLANEOUS ACCESSORIES

5-03111-00	Camera Holder F
5-63061-00	Release 30
5-63062-00	Release 50

## CASES

4-60862-01	Case L for FTb (for 55mm f1.2 lens)
4-60861-01	Case S for FTb (for 50mm f1.4, 50mm f1.8 lens)

## MACROPHOTO & CLOSE-UP ACCESSORIES

4-20601-20	Copy Stand 4
4-25901-03	Handy Stand F55 set
4-26201-20	Photo Micro Unit F
4-25117-00	Macro Hood
4-25501-00	Microphoto Hood

**PLEASE NOTE:** For further information on accessories please see the sections as follows:  
**Sect. 2: Canon Interchangeable Lenses**

## CODE NO. DESCRIPTION

4-25301-01	Extension Tube ABC Set
4-25301-00	Extension Tube A
4-25302-00	Extension Tube B
4-25303-00	Extension Tube C
4-25304-00	Extension Tube 25
4-25305-00	Extension Tube 50
4-25311-00	Extension Tube 75
4-25312-00	Extension Tube 100
4-25313-00	Extension Tube 150
4-25314-00	Extension Tube 200
4-25315-00	Extension Tube FL15
4-25321-00	Extension Tube FL25
4-25316-01	Extension Tube M Set
4-25316-00	Extension Tube M5
4-25317-00	Extension Tube M10
4-25322-00	Extension Tube M20
4-25403-00	55 Macrophoto Coupler
4-25404-00	58 Macrophoto Coupler
4-25405-00	48 Macrophoto Coupler
4-25701-00	FL48 Macrophoto Coupler
4-25711-00	FL58 Macrophoto Coupler
4-25721-00	FL55 Macrophoto Coupler
5-42011-00	Lens Mount Converter A
5-42021-00	Lens Mount Converter B
5-42031-00	Lens Mount Converter E
5-42071-00	Lens Mount Converter P
5-43231-01	58 Close-Up 450
5-43241-01	58 Close-Up 240
5-43251-01	48 Close-Up 450
5-43331-01	48 Close-Up 240
5-43571-00	55 Close-Up 450
5-43561-00	55 Close-Up 240
5-59042-20	Bellows FL
5-59043-00	Bellows M
5-59181-00	Slide Duplicator 48
5-59181-01	Slide Duplicator 55
43-6370	Attachment Ring 48 for Slide Duplicator
43-6371	Attachment Ring 55 for Slide Duplicator
43-6372	Attachment Ring 58 for Slide duplicator

## BODY COVER

4-52021-00	Camera Cover R-F
------------	------------------

## STRAP

5-61141-00	Neck Strap 7 with pad
------------	-----------------------

**Sect. 3: Canon F-1 System and SLR Accessories**  
**Sect. 9: Miscellaneous Accessories Cross-Referenced**  
 (including Canon Filters, Cases, etc.)