

CODE NO. ITEM
1-20821-23 Canon EX Auto w/lens EX 50mm
f/1.8 in case

Canon EX AUTO



The SLR That's Fun For Everyone



SPECIFICATIONS

- **Type:** 35mm single-lens reflex camera with automatic exposure
- **Picture Size:** 24x36mm
- **Lens:** front component convertible type with thread mount; EX 50mm f/1.8 lens standard
- **Interchangeable Lens Components:** EX 35mm f/3.5 (wide-angle), EX 95mm f/3.5 (telephoto) and EX 125mm f/3.5 (telephoto)
- **Viewfinder:** eye-level, using pentagonal prism; aerial image screen type, combined with microprism focusing aid
- **Viewfinder Information:** exposure indicator, f/stop scale and over/under-exposure warning marks; Angle Finder A2 and B can be attached.
- **Magnification:** 0.9x magnification
- **Mirror:** shockless instant-return type
- **Shutter:** cloth focal plane shutter with speeds from 1/500 sec. to 1/8 sec., B and X synchronization at 1/60 sec.
- **Electric Eye Mechanism:** fully coupled to film speed, shutter speed dial and aperture setting; Variable Aperture (shutter preferred) automatic exposure control. Diaphragm closes to proper f/stop when shutter button is pressed.
- **Exposure Meter Coupling Range:** EV4.75 (f/1.8, 1/8 sec.) to EV17 (f/16, 1/500 sec.) with ASA 100 film and standard f/1.8 lens; EV6.75 (f/3.5, 1/8 sec.) to EV17 (f/16, 1/500 sec.) with f/3.5 lenses
- **Film Speed Scale:** ASA 25-800
- **Exposure Meter:** through-the-lens system; CdS photocell just above the eyepiece measures light passing through the taking lens at maximum aperture. Total picture area is measured, with emphasis on central section.
- **Manual Control of Aperture:** possible at any desired f/stop by releasing the EE mechanism and turning the aperture ring
- **Flash Photography:** automatic flash with the Canolite D electronic flash unit (optional); Conventional flash photography performed with manually-operated aperture.
- **Power Source:** one 1.3V M20 (#625) mercury battery
- **Flash Contact:** direct-type (hot shoe) CAT signal contact
- **Flash Synchronization:** X contact; synchronization possible for FP, M and MF flash bulbs and electronic flash units
- **Film Rewinding:** by button and crank
- **Winding Lever:** 174° single-stroke operation; ratchet winding possible
- **Self-Timer:** built-in; Wound self-timer is actuated by pressing shutter button.
- **Film Loading:** Exclusive Canon QL film loading makes loading any standard 35mm cassette simple.
- **Frame Counter:** self resetting, actuated by opening camera back
- **Size:** 143x92x84mm (5 $\frac{5}{8}$ "x3 $\frac{3}{8}$ "x3 $\frac{1}{4}$ "')
- **Weight:** 900 g (1 lb., 15 $\frac{3}{4}$ oz.) with 50mm standard lens

ACCESSORIES

LENSES

CODE NO.	DESCRIPTION
2-25031-21	Canon lens EX35mm f3.5 w/hood in case
2-27061-21	Canon lens EX95mm f3.5 w/hood in case
2-27072-21	Canon lens EX125mm f3.5 w/hood in case

DIOPTRIC ADJUSTMENT LENSES

5-05072-00	Dioptric Adjustment Lens S (+3)
5-05073-00	Dioptric Adjustment Lens S (+2)
5-05051-00	Dioptric Adjustment Lens S (+1.5)
5-05075-00	Dioptric Adjustment Lens S (+1)
5-05076-00	Dioptric Adjustment Lens S (+0.5)
5-05041-00	Dioptric Adjustment Lens S (0)
5-05078-00	Dioptric Adjustment Lens S (-0.5)
5-05079-00	Dioptric Adjustment Lens S (-2)
5-05081-00	Dioptric Adjustment Lens S (-3)
5-05082-00	Dioptric Adjustment Lens S (-4)

GADGET BAGS

4-80024-00	Gadget Bag 4
4-80025-00	Gadget Bag G-1

MISCELLANEOUS ACCESSORIES

5-00242-20	Canolite D
5-40712-00	Angle Finder A-2
5-40711-00	Angle Finder B
5-40701-22	Magnifier S
5-41041-00	Magnifier Adapter S
5-03111-00	Camera Holder F
5-63061-00	Release 30
5-63062-00	Release 50

CASE

4-60741-01	Case for EX Auto
------------	------------------

MACROPHOTO & CLOSE-UP

4-20601-20	Copy Stand 4
5-43251-01	48 Close-Up 450
5-43331-01	48 Close-Up 240

STRAP

5-61141-00	Canon Neck Strap 7 with pad
------------	-----------------------------

PLEASE NOTE: For further information on accessories please see the sections as follows:

Sect. 3: Canon F-1 System and SLR Accessories
Sect. 9: Miscellaneous Accessories Cross-Referenced
(including Canon Filters, Cases, etc.)