

WISTA45SP



The Professional Photographer's Advantage

WISTA45SP

FEATURES:

The Wista 45-SP camera was designed with ease of use the primary concern. The theory was: even if the camera has an abundance of movements, without operational features to easily utilize them, they would go unused. Therefore, even the precision movements of the 45-SP camera have been made simple to use.

The 45-SP camera was specifically designed for enlarged front movements. The 45-SP allows the professional photographer the abundant and exact movements required for photography of the highest technical quality.

The adoption of a friction device allows precise micro tilt adjustments and greatly reduces the time necessary for tilt setting.

The friction device minimizes vibration of the U-arm even when the lock knob is loose. This eliminates distortion and damage to the U-arm and slide mechanism due to vibration.

The Wista 45-SP features a fresnel lens which combines with a ground focusing glass for brilliant corner to corner screen images.

This is one of four cameras in Wista's 45 series. The other three, the 45-N, 45-D and 45-RF cameras share many of the same fine features and specifications.

The 45-series cameras were specifically designed to simplify handling and use and are indeed all purpose professional tools.

SPECIFICATIONS

FORMATS:

- ☐ 4x5 in. International standard
- ☐ 6x9cm Rollfilm (optional)
- ☐ 5x7 Back adapter (optional)

BODY:

- ☐ Light die-cast alloy

BELLOWS:

- ☐ Leather bellows standard
- ☐ Leather bag bellows (optional)
- ☐ Leather extension bellows 600mm (optional)

IMAGE SIZE:

- ☐ 98x120cm

FILM:

- ☐ Sheet film
- ☐ Polaroid pack film

LENS MOUNT:

- ☐ Linhof-type/accepts WISTA or Linhof boards

BED SECTION:

- ☐ When opened the camera bed will automatically lock at 90 degrees
- ☐ Triple extension frame; minimum extension 66mm, standard maximum extension 300mm, 600mm with extension rails and bellows (optional)

CAMERA BACK:

- ☐ Interchangeable 4x5 adapter and rollfilm slide adapter (with automatic aperture control device)
- ☐ Focus glass interchangeable
- ☐ Rollfilm holder (6x9 or 6x7cm) adaptable
- ☐ 360 degree revolving back with 0-detents every 90 degrees

FRONT MOVEMENTS:

- ☐ Rise: 56mm (gear operated)
- ☐ Swing: 15 degrees (horizontally)
- ☐ Tilt: 15 degrees (forward & backward) w/friction drive
- ☐ Shift 40mm w/friction locks & 0-detents on focal axis

BACK MOVEMENTS:

- ☐ Swing 15 degrees (horizontally)
- ☐ Tilt: 90 degrees (forward), 15 degrees (backward)
- ☐ Micro focus: 4 degrees (backward)
- ☐ Micro swing: 4 degrees (left of right)

DIMENSIONS:

- ☐ Height: 180mm/8 in.
- ☐ Width: 197mm/8.75 in.
- ☐ Depth: 105mm/4.66 in.
- ☐ Weight: 2.9 kgs/6.3 lbs. (body only)

STANDARD FEATURES:

- ☐ Accessory shoe, leather strap, tripod hole, infinite distance stopper, flash gun shoe, distance scale for 135mm lenses

ACCESSORIES:

- ☐ Lenshood/bellows-type, reflex viewer magnifier, extension bellows and rails, camera and accessory case, rollfilm holders, 5x7 in back adapter, cable release, interlock cables & shutter