## Update & Add 'Macro-Focus' to Your Cooke Speed Panchros.



#### Features:

- Macro Focus capability: See chart below.
- Mount: Stainless steel Arri PL.
- Focus Ring: Large geared ring, compatible with Arri follow-focus system.
- Iris Ring: Geared for easy hand or automatic motor control. Scales in large clear engravings.
- 80mm Diameter Front: Compatible with today's popular lens accessories.
- T-stop Calibrations.
- Oversized Scales: Clear and brightly colored.
- Housing: All new lightweight aluminum alloy.

# Century Precision's Series 2000 Cooke Speed Panchro Conversion will revitalize & provide new innovative features for your lenses.

#### 'Macro-Focus'.

We offer the only Cooke Speed Panchro Update Conversion with 'Macro-Focus.' Especially handy for table-top cinematography, this feature enables ultra-close focusing. While one turn of the focus ring yields normal studio-type calibration, a second turn effects the macro capability. Thus, the 18mm focuses down to 1.75"!

#### Your Optics-Our Housing.

To maintain the famous Cooke Speed Panchro 'look', we use your lens barrel and internal iris assembly. Everything else is new—the focusing helix, focus and iris control rings, pins, screws and the entire external lens housings.

### PL Mount, Large Engravings, & Arri System Compatibility.

Your updated Panchros will feature stainless steel PL mounts, integral focus and iris gears, and 80mm fronts to accept Arri accessories. The lenses are outfitted with T-stops and large, clear, brightly-colored focus and iris scales.

#### Series 2000 Quality.

In keeping with our Series 2000 project, each lens is updated with the highest quality components and hand-crafted for precision alignment and long life.

All Century Precision Products feature an unconditional 30-day money-back guarantee.

1-800-228-1254

muy precision optics

10713 Burbank Bl, N. Hollywood, CA 91601 Tel: 818-766-3715 Fax: 818-505-9865

Lens	Century #	MOD from Front Element	MOD from Film Plane	Max. Aperture	Min. Aperture
18mm	CM-CK18-AL	1 3/4"	5 5/8"	T2.2	22
25mm	CM-CK25-AL	1 1/4"	5 1/2"	T2.2	22
32mm	CM-CK32-AL	1 7/8"	6 3/4"	T2.3	22
40mm	CM-CK40-AL	1 11/16"	7"	T2.3	22
50mm	CM-CK50-AL	1 9/16"	8"	T2.3	22
75mm	CM-CK75-AL	10 1/8"	16"	T2.3	22
100mm	CM-CK10-AL	8 1/4"	16 1/2"	T2.8	22