


Canon SCOOPIC 16M



Specifications

Type	16mm EE mechanism movie camera with macro zoom lens
Film	16mm single or double perforated film of 100 ft. (30.5m)
Lens	: Focal length 12.5 ~ 75mm, zoom ratio 6:1, lens speed T2.5 (f/1.8), 16 elements in 12 components, front thread 72mm P 0.75, outer diameter 75mm, minimum object distance 1.1m (3' 7-5/16"), range of macro-operation 80 ~ 750mm (from front vertex), multi-point focus is possible
Automatic EE system	Servo-controlled by CdS photocell and micromotor manual control is also possible, EE Coupling Range ASA 640, T2.5, 16 fps — ASA 20, T22, 64 fps not coupled to single frame and MACRO shooting
Film Speed	: ASA 20 ^(25 32) 40 ^(50 64) 80 ^{100 125} 160 ^(200 250) 320 ^(400 500) 640
Filming Speed	: Single frame, 16, 24, 32, 48, 64 fps, shutter opening angle 170°
Film Drive	By a built-in DC micromotor, speed is controlled by electronic governor
Power Source	An exclusive 12 V NiCd battery for film drive and automatic aperture control, a fully charged battery runs 16 rolls of 100 ft. film at 24 fps., external batteries can also be used
Film Loading	Semi-automatic, just insert the film tip into the film guide
Zoom & Focus	Manual
Viewfinder	Single-lens reflex type with all-matted focus glass, contains TV frame line, T/stop scales, over/under exposure warning marks, meter needle, etc., eyepiece is adjustable (-4 to +2 diopter), with eyepiece shutter to prevent the backflow of light
Footage Counter	: Counts exposed footage, automatically returns to "S" when side cover is opened, frame counter, 40 frames in one rotation (1 ft.)
Others	Film slack correction knob, accessory shoe, battery checker, shutter running lock
Size	287 x 230 x 153mm (11-5/16" x 9-1/16" x 6")
Weight	: 3.3 kg (7.3 lbs.) Set 8.5 kg (18.7 lbs.)
Battery Charger	Input voltage selector 100, 110, 120, 200, 220 and 240 V changing time 3.5 hours at normal temperature.

Subject to alterations.

Canon

CANON INC. 9-9, Ginza 5-chome, Chuo-ku, Tokyo 104, Japan

U.S.A.
NEW YORK — CANON U.S.A., INC.
 10 Nevada Drive, Lake Success, Long Island, N.Y. 11040, U.S.A.
MANHATTAN — CANON U.S.A., INC.
 600 Third Avenue, New York, N.Y. 10016, U.S.A.
CHICAGO — CANON U.S.A., INC.
 457 Fullerton Avenue, Elmhurst, Illinois 60126, U.S.A.
LOS ANGELES — CANON OPTICS & BUSINESS MACHINES CO., INC.
 3113 Wilshire Blvd., Los Angeles, California 90010, U.S.A.

CANADA
TORONTO — CANON OPTICS & BUSINESS MACHINES CANADA LTD.
 3245 American Drive, Mississauga, Ontario, Canada

EUROPE, AFRICA
& MIDDLE EAST
AMSTERDAM — CANON AMSTERDAM N.V.
 Gebouw 70, Schiphol, Oost, Holland

CENTRAL &
SOUTH AMERICA
PANAMA — CANON LATIN AMERICA, INC.
 Apartado 7022, Panamá 5, República de Panamá