



Fresnel Kits

Fresnel kits bring studio quality lighting to field production. Featuring rugged, lightweight ARRI 300W and 650W Fresnels, these kits provide the controlled lighting required for high quality video and film production.

ARRI Fresnel kits include barndoors, scrims, stands and lamps, all protected by our Heavy Duty Shipping Case.



650/4 Fresnel kit

4	L1.79250.B	650W fresnel
4	L2.79470.0	barndoor
4	L2.79490.0	filter frame
4	506440	FRK lamp
4	506450	full single scrim
4	506452	full double scrim
4	570050	AS2 stand
1	571195	heavy duty case

weight 70 lbs.

300/4 Fresnel kit

4	L1.79000.B	300W fresnel
4	L2.79170.0	barndoor
4	L2.79190.0	filter frame
4	503440	FKW lamp
4	503450	full single scrim
4	503452	full double scrim
4	570050	AS2 stand
1	571195	heavy duty case

weight 70 lbs.

650/300 Fresnel kit

2	L1.79000.B	300W fresnel
2	L2.79170.0	barndoor
2	L2.79190.0	filter frame
2	503440	300W FKW lamp
2	503450	5" full single scrim
2	503452	5" full double scrim
2	L1.79250.B	650W fresnel
2	L2.79470.0	barndoor
2	L2.79490.0	filter frame
2	506440	650W FRK lamp
2	506450	6 5/8" full single scrim
2	506452	6 5/8" full double scrim
4	570050	AS 2 stand
1	571195	heavy duty case

weight 73 lbs

650 Arrilite/Fresnel kit

2	L1.79250.B	650W fresnel
2	L2.79470.0	barndoor
2	L2.79490.0	filter frame
2	506440	650W FRK lamp
2	506450	6 5/8" full single scrim
2	506452	6 5/8" full double scrim
2	L1.76700.G	Arrilite 650
2	L2.76973.0	barndoor
2	571140	650W FAD lamp
2	571150	7 1/4" full single scrim
2	571152	7 1/4" full double scrim
4	570050	AS 2 stand
1	571195	heavy duty case

weight 76 lbs



ARRIFLEX CORPORATION

500 ROUTE 303, BLAUVELT, NY 10913 TWX 7105752624
600 NO. VICTORY BLVD., BURBANK, CA 91502 TWX 9104984641

FAX (914) 425-1250
FAX (818) 848-4028

(914) 353-1400
(818) 841-7070

ARRI®

FRESNELS

**RUGGED
OPTIMISED OPTICS
MODERN STYLING**

**COMPACT SHAPE
SUPERIOR COOLING
FULL RANGE OF ACCESSORIES**

ARRI 300W

PHOTOMETRIC DATA: @16.4 ft

Weight: 3.4 lbs
Size: 6.3" (L) 7.1" (W) 10" (H)
Lens: 3.15"
Lamp: 300W CP 81 (120V)

	SPOT	FLOOD
Beam Angle	14°	60°
Beam Diameter	2.3 ft	11.5 ft
Intensity	91 fc	16 fc

ARRI 650W

PHOTOMETRIC DATA: @16.4 ft

Weight: 4.9 lbs
Size: 7.5" (L) 8" (W) 10.8" (H)
Lens: 4.33"
Lamp: 650W CP 89 (120V)

	SPOT	FLOOD
Beam Angle	20°	60°
Beam Diameter	3.6 ft	11.5 ft
Intensity	153 fc	36 fc

ARRI 1000W

Manual or pole operation

PHOTOMETRIC DATA: @16.4 ft

Weight: 8.3 lbs
Size: 8.9" (L) 10" (W) 13.6" (H)
Lens: 5.1"
Lamp: 1000W EGT

	SPOT	FLOOD
Beam Angle	12°	59°
Beam Diameter	2 ft	11 ft
Intensity	395 fc	56 fc

ARRI 2000W

Manual or pole operation

PHOTOMETRIC DATA: @16.4 ft

Weight: 13.4 lbs
Size: 10.2" (L) 12" (W) 14.8" (H)
Lens: 6.9"
Lamp: 2000W CYX

	SPOT	FLOOD
Beam Angle	14°	60°
Beam Diameter	3.9 ft	19 ft
Intensity	534 fc	111 fc

ARRI 5000W

Manual or pole operation

PHOTOMETRIC DATA: @33 ft

Weight: 24.6 lbs
Size: 13.6" (L) 16.3" (W) 20.5" (H)
Lens: 9.85"
Lamp: 5000W DPY

	SPOT	FLOOD
Beam Angle	15°	60°
Beam Diameter	8.5 ft	37.7 ft
Intensity	525 fc	163 fc

