

Canon

New Product Announcement

January 1, 1986

C21-9172

Canon Lens FD 80-200mm f4.0L

FD 80-200mm f4.0L

This tele-zoom in the line of superb "L" Series lenses features both fluorite and UD (ultra dispersion) glass for extraordinary suppression of spectral aberrations. In addition, it features reduced flare, a built-in macro mode and is lighter and more compact than the conventional FD 80-200mm f4.0 lens. Yet, this is one of the most affordable lenses in the Canon "L" Series line.



SPECIFICATIONS

Type: Tele-zoom w/Macro
Construction: 14 elements
in 12 groups
Angle of view: 30°-12°
Minimum Aperture: f32
Closest Focusing Distance:
Normal—1.2m (3' 11¹/₄"")
Macro—0.95m (3' 1³/₈"")
Filter Size: 58mm
Lenshood: Optional, BT-58
(C44-5802)
Length: 153mm (6¹/₄"")
Weight: 675g
(1 lb., 8¹/₈ oz.)
Cap: C58 (CG2-0072)
Case: Optional, LH-C19,
(C47-0961), LS-B21
(C47-0956)
Function: Auto aperture,
full aperture metering,
AE operation with all
Canon Automatic SLR
cameras
Coating: Super Spectra

C21-9162

Canon Lens FD 100-300mm f5.6L

FD 100-300mm f5.6L

This new lens was developed in combination with the FD 100-300mm lens in order to provide Canon's superb "L" Series technology at a more affordable price. By using Fluorite and UD (Ultra Dispersion) elements instead of conventional optical glass, spectral aberrations are greatly suppressed yielding sharper images.



SPECIFICATIONS

Type: Tele-zoom w/Macro
Construction: 15 elements
in 10 groups
Angle of view: 24°-8°15'
Minimum Aperture: f32
Closest Focusing Distance:
Normal—2m (6' 6³/₄"")
Macro—1m (3' 3⁵/₁₆"")
Lenshood: Optional, BT-58
(C44-5802)
Length: 172mm (6¹³/₁₆"")
Weight: 710g (1 lb., 9³/₈ oz.)
Cap: C58 (CG2-0072)
Case: Optional, LH-C21
(C47-1081), LS-B21
(C47-0956)
Function: Auto aperture, full
aperture metering, AE operation
with all Canon Automatic SLR
cameras
Coating: Super Spectra

Canon

New Product Announcement

January 1, 1986

C21-9163

FD 100-300mm f5.6

Canon Lens FD 100-300mm f5.6

Designed in conjunction with the FD 100-300mm f5.6L lens, this new lens is lighter and more compact than the previous FD 100-300, yet provides the same high optical performance. Its 3x zoom range in this focal length makes it versatile enough to use with such diverse subjects as portraits, candid, sports and nature and its macro mode enables exciting closeup photography.



SPECIFICATIONS

Type: Tele-zoom w/Macro

Construction: 15 elements
in 9 groups

Angle of view: 24°-8°15'

Minimum Aperture: f32

Closest Focusing Distance:

Normal—2m (6' 6³/₄")

Macro—1m (3' 3⁵/₁₆")

Lenshood: Optional, BT-58
(C44-5802)

Length: 172mm (6¹³/₁₆")

Weight: 705g (1 lb., 9³/₄ oz.)

Cap: C58 (CG2-0072)

Case: Optional, LH-C21
(C47-1081), LS-B21
(C47-0956)

Function: Auto aperture, full
aperture metering, AE operation
with all Canon Automatic SLR
cameras

Coating: Super Spectra

Subject to change without notice.