

Electronically-controlled focal plane shutter of titanium! Captures even the quickest movement at 1/2000 s.

Nr58721

Powerful winder! For single exposures or sequential pictures at a speed of 1.3 frames/s.

ELBLAD

Extremely fast lenses! Allow for maximum utilization of fast shufter speeds, increasing the amount of light in the viewfinder and aiding composition and focusing.

Lenses with built-in leaf shutters! Provide flash synchronization at all speeds down to 1/500 s and function at any shutter speed independent of the battery.

The $2^{1}/4 \times 2^{1}/4$ format! A guarantee for superb image quality.

The Hasselblad 2000FCW has features that make it ideal for handling situations where anything can happen, quickly and unexpectedly.



Photo: Mats Lindgren





Photo: Jens Karlsson

Film magazines

Load, change film type or format in just a matter of seconds. You have 8 magazines to choose from. For $2^{1/4} \times 2^{1/4}$, $2^{1/4} \times 1^{5/8}$ and $1^{5/8} \times 1^{5/8}$ with a capacity of up to 200 exposures. For roll film, Polaroid film and sheet film. One magazine is a data recording magazine.



Winder

It is as easy to attach the Hasselblad Winder as it is to remove the winding crank. The 2000FCW is transformed into an efficient motorized camera with a shooting capacity of 1.3 frames per second.



Snutter speea multiplier Multiplies all of the focal plane shutter's 23 speeds by a factor of 60 enabling you to use speeds from 1 s to 60 s for those really long exposures.

Viewfinders

Focusing hoods or prism viewfinders with or without TTL-metering. They enlarge the viewfinder image up to 3 times. A total of 5 different types. Plus a sports viewfinder and a range viewfinder.

Focusing screens

Made of glass that you can write on directly or with central grid, split image and checked pattern in several different combinations. Eight focusing screens that are easily and quickly changed without tools.

Grips

The camera can easily be hand-held the way it is. If another grip is desired, then such alternatives as the pistol grip or the flashgun bracket are available. A quickcoupling is available for tripod attachment that really lives up to its name.





The Hasselblad 2000FCW is an integral part of a camera system with over 300 components. Several of these are shown here. The others can be found in the Hasselblad Product Catalog. Request a copy at your local photo store.







Close-up accessories

A different and intriguing world of camera subjects lies inside of the close limit of a lens. With extension tubes, automatic bellows, Proxars and other special accessories, you'll be able to get close to the details.







Lenses

A total of 22 lenses are compatible with the 2000FCW. Focal lengths from the 30mm fish-eye to the 500mm tele. Telephoto focal lengths can be enlarged twice with the Zeiss Mutar Teleconverter. The professional lens shade can be attached to lenses with focal lengths from 60 to 250 mm.











Photo: Ulf Sjöstedt

Photo: Jens Karlsson

The photographer that took these sailboat pictures needed the fast shutter speed to achieve clean, sharp images while shooting from the swaying, reeling escort boat. And he needed the large format for any eventual posters. At the same time he wanted a camera that was compact and easy to work with. He chose the Hasselblad 2000FCW.

With the Hasselblad 2000FCW, you are equipped with the technical prerequisites for taking pictures of superior quality under the most varying circumstances. And you have a camera that works just as well in the studio as it does out in the field.

055-3

E-2244

Photo: Mats Lindgren

I-10148

I-10148

HASSELBLAD **2000FCW**



Technical specifications and equipment

and the second	
Camera type:	Single-lens reflex camera with $2^{1/4} \times 2^{1/4}$ film size (max.) and built-in focal plane shutter.
Design:	Electromechanical design with light metal camera body shell cast in one piece.
Viewfinder:	Non-vignetting viewfinder image. Folding focusing hood. The camera can accept different types of focusing screens, prism viewfinders with or without a built-in light meter, focusing hood, or sports viewfinder.
Film advance:	Manual advance with winding crank. Automatic with the Hasselblad Winder.
Shutter:	Horizontal focal plane shutter of titanium with speeds to 1/2000s. With CF-lenses, built-in leaf shutter with speeds to 1/500s. Camera operation is then independent of the battery.
Flash synchronization:	Focal plane shutter with X synchronisation at 1/90s and slower shutter speeds.
Battery/capacity:	6 V PX-28 type. Fresh battery good for 20,000 exposures.
Tripod socket:	3/8" socket thread and tripod plate for quick-coupling attachment.
External dimensions:	Camera body only—see opposite side. The camera body with 80mm Planar F-lens and magazine A 12: $180 L \times 114 W \times 107 H mm (7 \times 4\frac{1}{2} \times 4\frac{1}{4} in)$.
Weight:	Camera body only: 730 g (1 lb 10 oz). The camera body with 80mm Planar F-lens and magazine A 12: 1560 g (3 lb 7 oz).
	The camera body (chrome model, product no. 10317 or black model, product no. 10333) comes with standard focusing screen, focusing hood, neck strap, and front and rear protective covers.
Accessories	
Lenses:	Interchangeable Hasselblad F-lens series without built-in shutters and CF-lens series with built-in leaf shutters. The CF-lens series has X synchronisation for electronic flash at all speeds to 1/500s.
Film magazines:	Interchangeable magazines for the following sizes: $2^{1/4} \times 2^{1/4}$, $2^{1/4} \times 1^{5/8}$, and $1^{5/8} \times 1^{5/8}$. Film types: 120, 220, 70 mm double-perforated film, sheet film, and Polaroid film.
	More information on other accessories in the Hasselblad Product Catalog. Right to changes without notice.

Cover picture: Glen Percival

Victor Hasselblad Aktiebolag

Box 220, S-401 23 Göteborg, Sweden

Exclusive U.S. distributor: VICTOR HASSELBLAD INC. 10 Madison Road Fairfield, New Jersey 07006

Production: Hasselblad/SP. Copyright © 1985 Victor Hasselblad AB. All right reserved. Printed in Sweden. Falkenbergs Tryckeri AB 85 218 95 04 1985