

TOPCON

TOPCON RE 300, 35mm SINGLE LENS REFLEX

Compact and versatile, the Topcon RE 300 provides uncomplicated picture taking and sharp color renditions. An advanced light emitting diode system (series of red or green lights in viewfinder noting under or over exposure) simplifies light metering and virtually guarantees the correct exposure. Other features include self timer, built-in hot shoe, automatic 55mm f/1.7 lens, CdS through the lens metering, split image rangefinder center spot in the viewfinder, and very short stroke film advance lever.

An efficient auto winder is available as an accessory, eliminating any need for manual film transport, if desired. Press the shutter button on the camera body and release and the film is automatically advanced to the next frame within 0.5 of a second. You'll never miss that decisive shot fumbling with the lever transport.



SPECIFICATIONS

Description	Topcon RE 300 35mm, Eye Level Single Lens Reflex.
Exposure System	Through-the-lens averaging type using two (2) CdS cells in pentaprism red LED's (light emitting diodes) above and below, center green LED indicates correct exposure; all LED's actuated by partially depressing shutter release. ASA range 25 to 1600 (DIN range 15-33).
Lens	55mm f/1.7 Topcon Lens.
Lens Mount	Topcon Bayonet.
Shutter	Vertically running, copal square shutter with speeds from one second to 1/1000 second, plus bulb, X sync at 1/125 second, built-in self timer, cable release socket.
Viewfinder	Eye level viewfinder with fixed pentaprism, fixed focusing screen with split image rangefinder center spot, ground glass collar and fresnel screen showing 91% of picture area, LED exposure indicator visible in viewfinder.
Synchronization	Synchronization for electronic flash (X) at 1/125 second. PC connector on front of body under shutter speed dial, or hot shoe connection.
Film Advance	Single, very short stroke with lever stand off.
Film Counter	Additive, automatic resetting.
Filter Size	52mm Screw in type.
Battery	Two (2) 1.5 volt silver oxide batteries required. (Eveready S-76 or equivalent.)
Dimensions	5½" x 3⅝" x 3½" (141mm x 91.5mm x 90mm) with lens. 5½" x 3⅝" x 2" (141mm x 91.5mm x 50mm) body only.
Weight	28 oz. (820g) with lens. 19.9 oz. (565g) body only.
Other	Case and lens cap included.
Accessories	Complete line of Topcon lenses and attachments, also Carenar 28mm, 35mm, 135mm, 200mm lenses available; Auto winder II.

AUTO WINDER II (To fit Topcon RE 300)

Batteries	Six (6) AA size manganese or alkaline manganese.
Auto Winding Speed	Approx. 0.5 second.
Shutter Speeds Usable	All shutter speeds from 1 to 1/1000 second, can be used with self-timer.
Shutter Release Action	Shutter release on camera body.
Indicator Lamp	Red LED remains illuminated during auto winding.
Dimensions	5 15/16" x 3⅝" x 2⅝" (150mm x 87mm x 69mm)
Weight	7 oz. (220g) without batteries. 12 oz. (340g) with batteries.

Specifications and/or minor modifications of styling subject to change without notice.

PAC

PHOTO AMERICA CORPORATION

Printed in USA

7491 N.W. 8th Street Miami, Florida 33126 305/266-6811