TOPCON

TOPCON RE 200, 35mm SINGLE LENS REFLEX

Light, compact, and versatile, the Topcon RE 200 is sure to be a hit with your customers. The bright viewfinder incorporates an advanced metering system containing two red (under-exposure, over-exposure) and one green (correct exposure) light emitting diodes (LED). Simply adjust exposure or shutter speed until the green diode lights up and shoot. Easy! Convenient design, and features such as self-timer, built-in hot shoe, automatic 55mm f/1.7 lens, CdS through the lens metering, and very short stroke film advance contribute to an ease of operation uncharacteristic of many SLR's today. Add to its many merits the internationally renowned reputation of Topcon quality, reasonable price, and numerous accessories available, and you'll find that the RE 200 is truly a system camera.



SPECIFICATIONS

Description

Exposure System

Lens Mo

Lens Mount Shutter

Viewfinder

Synchronization

Film Advance Film Counter Filter Size Battery Dimensions

Weight Other

Accessories

Topcon RE 200, 35mm, eye-level single lens reflex.

Through-the-lens averaging type using two (2) CdS cells in pentaprism, red LED's (light emitting diodes) above and below, center green LED indicates correct exposure; all LED's actuated by partially depressing shutter release. ASA range 25 to 1600 (DIN Range 15 to 33).

55mm f/1.7 RE Topcor lens.

Topcon Bayonet Mount.

Vertically running, copal square shutter with speeds from one second to 1/1000 second, plus bulb, X sync at 1/125 second. Built-in self-timer. Cable release socket.

Eye-level viewfinder with fixed pentaprism, fixed focusing screen with microprism center spot, ground glass collar, and fresnel screen showing 91 percent of picture area, LED exposure indicator visible in viewfinder.

Synchronization for electronic flash (X) at 1/125 second. PC connector on front of body, under shutter speed dial, or hot shoe connection.

Single, very short stroke, with lever stand off.

Additive, automatic resetting.

52mm screw-in type.

Two (2) 1.5 volt silver oxide batteries required. (Eveready S-76 or equivalent). $5\frac{1}{2}$ " $x3\frac{5}{8}$ " $x3\frac{1}{2}$ " (141mm x 91.5mm x 90mm) with lens; body only, $5\frac{1}{2}$ " $x3\frac{5}{8}$ " x2"

(141mm x 91.5mm x 50mm). 28 oz. (820g) with lens; 19.9 oz. (565g), body only.

Case and lens cap included.

Complete line of Topcor lenses and attachments; also Carenar 28mm, 35mm, 135mm, 200mm lenses available.



Specifications and/or minor modifications of styling subject to change without notice.

PHOTO AMERICA CORPORATION

7491 N.W. 8th Street Miami, Florida 33126 305/266-6811