Rollei XF35



The new Rollei XF35 for perfect pictures without worry. New fully automatic 24 x 36mm compact camera.

The Rollei XF35 is a compact, high-performance 35mm camera with programmed CdS exposure automation with shutter speeds from 1/650 to 1/30 second and apertures from f/2.3 to f/16, settings visible in the view-finder, a coupled rangefinder, automatic flash control, self-timer and hot-shoe flash contact.

A superior lens is a pre-requisite for really sharp pictures. Rollei, therefore, developed a 5-element high-quality lens for the Rollei XF35.

The famous and proved Sonnar lens type now appears in a compact camera as the 40mm Sonnar* f/2.3, made by Rollei, to guarantee first class pictures.

Technical Data

Camera type: Fully automatic compact 35mm range-finder camera with automatic exposure control.

- Lens: 40mm Sonnar* f/2.3 (5 elements, 4 groups) with M 46 x 0.75 screw-in filter fitting.
- Rangefinder: Coupled coincidence type rangefinder.
- Nearest focusing distance: 3.5 feet (1 metre).
- Shutter: Leaf shutter, 1/650 to 1/30 second and B.
- *This lens manufactured by the Rollei Group under license from Carl Zeiss, Oberkochen, West Germany.

- Exposure metering: Automatic program with CdS cell.
- Aperture range: f/2.3 to f/16.
- Meter measuring range: EV 7.5 to 17 with 100 ASA (21 DIN) film (equivalent to 20-16,000 cd/sq.m.).
- Film speed setting range: 25 to 400 ASA (15 to 27 DIN).
- Automatic flash control: Aperture and distance setting automatically coupled after preselecting the guide number.
- Flash outlet: Hot-shoe (X-synchronized).
- Finder signals: Meter needle to indicate aperture/speed combinations, red underexposure warning, bright-line finder with parallax marks.
- Release: Release button with cable release socket.
- Self-timer: Delay approx. 10 seconds.
- Frame-counter: Counts forward from No. 1 to 36, resets itself on film changing.
- Film loading: Clamping take-up spool.
- Battery: Single 1.35 volt cell (PX 625 or equivalent).
- Tripod bushing: 1/4 -20.
- Eyelets: On both sides, for wrist strap.
- Size: Approx. 4.4 x 2.8 x 1.25 inches (112 x 71 x 32mm).
- Weight: Approx. 12½ ounces (355 grams).
- Accessories: Soft leather case and lens cap.