

## NIKON REFLEX CAMERA Price List

# NIKON Price List

Reflex Cameras & Accessories • Nikkor Lenses NIKON Inc. • 111 FIFTH AVE., NEW YORK 3 • ORegon 4-7970

#### REFLEX CAMERA

**Retail List** WITH EXCISE TAX WHEN APPLICABLE

NIKON "F" AUTOMATIC REFLEX CAMERA - 35mm; 36 exposure, 1 x 1½. Available with interchangeable Photomic Finder (Nikon F Photomic) combining a meter and prism finder in one housing - or with a conventional pentaprism eyelevel finder. Features instant return automatic mirror and instant reopen automatic diaphragm; built-in depth-of-field preview control; built-in ground glass rangefinder - interchangeable with other types of ground glasses. Provision for locking mirror up. Accepts electric motor drive, accessory waist level finder. 13 shutter speeds, click-stop, from 1 to 1/1000 plus T & B, on single non-rotating dial; full synch plus electronic flash at 1/60; auto zero reset exposure counter; calibrated delayed action self timer; removable back; fixed take up spool; single stroke rapid film advance; high speed film rewind; tripod socket built into camera body.

CA1520	Nikon F. Photomic Body, chrome	285.00
CA1521	Nikon F. Photomic, chrome, with 50mm f2.0 auto	375.00
CA1522	Nikon F. Photomic, chrome, with 50mm f1.4 auto	440.00
CA1525	Nikon F, Photomic Body, Black	304.50
CA1526	Nikon F, Photomic, Black with 50mm f2.0 Auto	394.50
CA1527	Nikon F. Photomic, Black with 50mm f1.4 Auto	459.50
CA1500	Nikon F. Body only: satin chrome finish	233.00
CA1501	Nikon F. satin chrome finish; w/50mm f2.0 Auto	323.00
CA1502	Nikon F. satin chrome finish; w/50mm f1.4 Auto	388.00
CA1505	Nikon F. Body only; satin black finish	252.50
CA1506	Nikon F. satin black finish: w/50mm f2.0 Auto	352.50
CA1507	Nikon F, satin black finish; w/50mm f1.4 Auto	407.50

NIKKOREX 'F' AUTOMATIC REFLEX CAMERA — 35mm; 36 exposures, 1" x 11/2". Features automatic instant return mirror and automatic instant reopen diaphragm; depth-of-field preview control. Fresnel-type focusing screen with split-prism rangefinder. Accepts 20 interchangeable Nikkor & Auto-Nikkor lenses. Accepts most Nikon F accessories. Accessory exposure meter couples to diaphragm & shutter; metal focal plane shutter; 13 shutter speeds, click-stop from 1 to 1/1000 plus T & B on single non rotating dial; 'M' (flashbulb) synch at all speeds, 'X' (Electronic flash) synch to 1/125; variable self timer delays action up to 10 seconds. Auto

#### REFLEX CAMERA

-Continued

**Retail List** WITH EXCISE TAX WHEN APPLICABLE

23.00

14.50

18.50

	et exposure counter; hinged back; fixed takeup spoot; single	
	pid film advance; high speed film rewind.	400.50
CA1800	Nikkorex F, Body Only	109.50
CA1801	Nikkorex F, with 50mm f2.0 Auto	199.50
CA1802	Nikkorex F, with 50mm f1.4 Auto	264.50
Camera Cas	es — Nikon F, Nikkorex F	
CC477	Leather Eveready Case for F Photomic — Brown	18.50
CC478	Leather Eveready Case for F Photomic — Black	23.00
CC476	Leather Eveready Case, semi-soft, for F Photomic — Black	23.00
	Leather Eveready Case for Nikon F — Brown	18.50

### CC485 Leather Eveready Case, for Nikkorex 'F', Brown ..... REFLEX LENSES

CC472 Leather Eveready Case for Nikon F — Black .....

CC475 Soft Leather Pouch Case for Nikon F — Black .....

NIKKOR LENSES - NIKKOR lenses for the Nikon F and Nikkorex F represent a full line of high speed, high resolution lenses in lightweight mounts. The 28, 35, 50, 105, 135 and 200 mm lenses are fully automatic, with internally coupled instant reopen diaphragms. All have click stops. All alass-to-air surfaces are anti-reflection coated. Front lens caps are included. Lenses from 105mm up are furnished with lenshoods. The addition of adapter coupler LNP2350 permits direct, accurate mounting of the 180mm, 250mm, 350mm, 500mm lenses on Nikon F and Nikkorex F

camero	18. Well and the second	
LN 245	50mm f2.0 Auto-Nikkor	90.00
	<b>50mm f1.4</b> Auto-Nikkor	155.00
LN 249	55mm f3.5 Micro Nikkor	175.00
LN 250	55mm f3.5 Micro Auto-Nikkor	189.50
	8mm f8 Nikkor Fisheye with Finder	
LN 231	21mm f4.0 Nikkor, Reflex mount	209.50
	Viewfinder for 21mm lens, Reflex mount	
CC 435	Lens case for 21mm f4.0 lens and finder	5.00

LN 237 28mm f3.5 Auto-Nikkor, in plastic case .....

	Retail List			Retail List
REFLEX LENSES—Continued	WITH EXCISE			ITH EXCISE
	TAX WHEN APPLICABLE			APPLICABLE
LN 240 35mm f2.8 Auto-Nikkor, in plastic case		12-volt	battery pack uses 8 "C" batteries. Motor drive is furnished com-	
LN 244 35mm f3.5 P.C. Nikkor		plete·w	with battery pack and connecting cord. Price includes installation.	
LN 275 43-86mm f3.5 Auto-Nikkor Zoom		Camer	a must be returned to us for fitting.	
LN 272 85mm to 250mm f4.0 Telephoto zoom Auto-Nikkor		EM10	Nikon Electric Motor Drive Model F36; for Nikon F Reflex	249.50
CC 450 Lens case, leather, for 85 to 250 zoom lens		EM11	Nikon Electric Motor Drive, Model F250; for Nikon F Reflex	489.50
LN 265 105mm f2.5 Auto-Nikkor, in plastic case		EMP17	Battery Pack, 12-volt, replacement, for EM10, 11	23.50
LN 266 105mm f4.0 Nikkor; preset diaphragm	74.50	EMP26	Connecting cord, 3', three-conductor for EM 10, 11	6.50
LN 271 135mm f3.5 Auto-Nikkor, in plastic case		EMP27	Connecting Cord, 30', three-conductor, for EM 10, 11	
LN 164 135mm f4.0 Nikkor, short mount		EMP33	Motor Relay Box; permits remote control of motor drive cameras with	
LN 175 200mm f4 Auto-Nikkor		LWII 00	intervalometer, or external switch, at various distances	25.50
CC 443 Leather Case for 200mm lens		AC2077	Film Cassette for 250 exposure back	
LN 277 200mm to 600mm f9.5 Zoom Auto-Nikkor			Spool Only, for AC2077	
LN 170 180mm f2.5 Nikkor, short mount, preset diaphragm	. 425.00 . 249.50		Film Winder, for loading AC2077	
LN 180 250mm f4.0 Nikkor, in short mount; semi automatic diaphragm		EMP31	1982 (2018) (1982) (1982) (1982) (1982) (1982) (1983) (1982) (1983) (1983) (1982) (1983) (1983) (1983) (1983) (1983) (1983) (1983) (1983) (1983) (1983) (1983) (1983) (1983) (1983)	
LN 185 350mm f4.5, Nikkor, in short mount; semi automatic diaphragm LN 193 500mm f5 Reflex Nikkor, with filters and case	CONTRACTOR OF STREET,	Limitor	operation; for 8-battery pack	9.50
LN 195 1000mm f6.3 Nikkor, in F mount		AC40	Pistol Grip, for all Nikon cameras; requires AC44 or AC46; provides	
LNP2350 Adapter Coupler, rotating, to adapt 180mm, 250mm, 350mm, 500mi			convenient camera-lens support, and trigger release	14.75
Short mount Nikkor lenses to Automatic Reflex		AC44	Micro Switch Unit, for use with electric motor drive in combination	
LNP2360 Adapter Coupler, F Lenses on 'C' Mount			with pistol grip AC40	21.00
LNP2352 Adapter Coupler, Leica lenses		AC46	Coupling Cable, for pistol grip-to-camera	
THE RESERVE AND ASSESSMENT OF THE PROPERTY OF		AC47	Adapter for Coupling Cable, Nikkorex F	1.25
REFLEX ACCESSORIES	\$1.00 m	EMP33	O Repeating Electronic Flash Unit for motor drive	
at at more property and the second of the second	20-415 W	EMP35	Wireless Control Unit for motor drive	450.00
NIKON PHOTOMIC FINDER SYSTEM — Combines an exposure meter an	d	EMP37		
prism finder in the same housing. Uses cadmium sulphide cell, couples	lo L/			
both shutter speed & lens diaphragm (of automatic lenses). 'Matc needle is visible in prism finder, permitting the setting of correct e	11 Y-	FINDERS A	AND FOCUSING SCREENS — for Nikon Auto Reflex F	
posures (as well as framing and focusing) without removing the ey	/e	VF230	1 Waist Level Finder; can be interchanged with eyelevel prism Finder;	;
from the finder. Can be removed & interchanged with standard Niko	on	10 700	complete with case	
F Prism. Supplied with converter tube and incident light attachment.	Hitter water a series	VF2321	1 Prism Assembly, complete for Nikon F	47.50
MR55 Photomic Finder System, Nikon F	THE RESIDENCE OF SHARE S	VF2331	Focusing Ground Glass, Model A; with rangefinder	17.50
MR50 Exposure Meter, Model 3, Nikon F		VF2332	2 Focusing Ground Glass, Model B; plain, with clear center, fine	;
MR77 Incident Light Attach. for Model 3	90	6 128	focus spot	. 13.50
MR80 Incident Light Attach. for Photomic	1.35	VF233		
AC81 Converter Tube, for Photomic	1.35		etch	
MR60 Nikkorex F Coupled Exposure Meter — couples to shutter speed d	ial	VF233	하게 돈을 하게 하는데 하는데 하는데 하는데 이번에 사용하는데 하는데 나는데 하를 하는데 하를 하는데	
and diaphragm (of automatic lenses)	27.50	VF233	5 Focusing Ground Glass, Model E, Plain, with fine vertical & horizontal	
MRP65 4X Light Amplifier	. 7.50	19	lines; clear, fine focus center spot .	. 17.50
NIKON PERIEV FIRSTRIC MOTOR PRIVE	100	FLASH FO	QUIPMENT	
NIKON REFLEX ELECTRIC MOTOR DRIVE — takes single frames, bur of 2 or more exposures or continuously through a full film load. Exposures	ire		<b>5H</b> — Compact BC unit fits accessory shoe on the Nikon F by means	5
firing rate may be varied up to 4 per second. Motor is housed in	an	of Co	upler FLP 364, makes electrical contact without requiring any wires.	
accessory back which is interchangeable with the standard camera back	ck.	Tilting	head reflector permits bounce flash and is a collapsing, fan-fold	1
数据 100 mm 100 m				

Dotail list

#### NIKON PRICE LIST

### REFLEX ACCESSORIES—Continued

Retail List
WITH EXCISE
TAX WHEN
APPLICABLE

H EXCISE
WHEN
LICABLE
Nikon Lens Hoods — Snap-on hoods may be "stored" in a

Retail List
WITH EXCISE
TAX WHEN
APPLICABLE

1.60

1.60

type. An exposure guide is built on to the back of the unit body. The BC-5 uses standard 22½ volt battery; built-in test bulb for checking camera circuit continuity and battery-capacitor charge; bulb ejector button. Supplied complete with leather carrying case.	ine ine
FL354 BC-5 Flash attachment	19.95
FLP355 Capacitor, power unit (replacement)	3.25
FLP364 Coupler for flash gun; required for mounting BC-5 or BC-6 on Nikon F	4.00
BC-6 FLASH — A compact BC unit fitting into the accessory shoe of the camera. Takes the small AG-1 flash bulb. Uses standard flash cord con- nection and 15-volt battery.	
FL356 BC-6 Flash Attachment, for F cameras	10.50
FLP365 Flash Shoe Adapter, required for mounting BC-6 on Nikkorex F	2.95
CONNECTING CORDS — for Nikon Automatic Reflex	
FLC374 8" Cord for camera w/Heiland type plug	2.75
FLC378 24" Cord for camera w/ Heiland type plug	3.25
FLC382 Coiled cord (4½') for camera w/Heiland type plug	4.95
NIKON 'F', NIKKOREX 'F' GUIDE — This comprehensive book describes both cameras in detail including their construction and operation. It also covers the lenses and accessories which are available.	121
BK2021 Nikon 'F', Nikkorex 'F' Guide, hard cover	2.50
NIKON FILM CASSETTES (Magazine)	
AC2075 Film Cassette for all Nikon Cameras	4.90
AC2077 Film Cassette for 250 exposure back	18.50
AC2079 Spool only for AC2077	4.25
AC2080 Film Winder, for loading AC2077	75.00
NIKON DEFLEY LENS HOODS FILTEDS LENS & BODY CAPS	

NIKON	KELLEX	FEMS	HOODS,	TILIEKS,	TEM2	Oc	PODI	CAPS

Quick Check Chart fo	r Nikkor L	ens Attachments	5 98808
	SNAP-ON HOOD	SNAP-ON LENS CAP	SCREW-IN FILTER
21mm f4.0 Reflex mount	see ACR507 .	52mm	52mm
28mm f3.5 Auto Reflex mount	see ACR508.	52mm	52mm
35mm f2.8 Auto Reflex mount	see ACR510.	52mm	52mm
50mm f2.0 Auto Reflex mount			
50mm f1.4 Auto Reflex mount	see ACR517	52mm	52mm
58mm f1.4 Auto Reflex mount	see ACR517.	52mm	52mm
105mm f2.5 Auto Reflex mount	see ACR516.	52mm	52mm
105mm f4.0 Reflex mount			
135mm f3.5 Auto Reflex mount	see ACR516 .	52mm	52mm

ikon Lens Hoods — Snap-on hoods may be "stored" in reverse position on the lens.	16. 16
ACR507 Lens Hood, screw in for 21mm. f4.0 Nikkor, in Reflex mount	5.25
ACR509 Lens Hood, screw in for 28mm f3.5 Auto Nikkor	5.25
ACR510 Lens Hood, screw in for 35mm. f2.8 Auto Nikkor	5.25
ACR515 Lens Hood, snap on, for 50mm. f2.0 Auto Nikkor	5.25
ACR516 Lens Hood, snap on, for 105mm., 135mm. Auto Nikkor	5.25
ACR517 Lens Hood, snap on, for 50mm, 58mm f1.4 Auto Nikkor	5.25
ACR519 Lens Hood, snap on, for 105mm f4.0	4.00
ACR616 Lens Hood, for 85-250mm., 200-600mm. Zooms	22.50
ACR610 Lens Hood, for 180mm. f2.5 Auto-Nikkor	17.60
ACR611 Lens Hood, for 250mm. f4.0 Auto-Nikkor	17.60
ACR612 Lens Hood, for 500mm. f5.0 Nikkor	31.00
ACR618 Lens Hood, for 350mm. f4.5 Nikkor	22.50
optical flats; hard-coated on both sides. Fits 21mm. f4.0, 28mm. f3.5, 35mm. f2.8, 50mm. f2.0, 50mm. f1.4, 58mm. f1.4, 105mm. f2.5, 135mm. f3.5, 200mm f4.0, Auto Nikkor lenses. Supplied in case. Medium Yellow, Green 1, Red, Orange, UV Haze, 85C, Skylite, 82A, 85B, ND-4X, ND-8X.	V)
- AC2229 Filter, Screw-in, 52mm, medium yellow	8.85
AC2230 Filter, Screw-in, 52mm, green 1	8.85
AC2231 Filter, Screw-in, 52mm, orange	8.85
AC2232 Filter, Screw-in, 52mm, U V haze	8.85
AC2233 Filter, Screw-in, 52mm, 85 C	8.85
AC2234 Filter, Screw-in, 52mm, Skylite	8.85
AC2235 Filter, Screw-in, 52mm, 82 A	8.85
AC2249 Filter, Screw-in, 52mm, red	8.85 8.85
	13.50
AC2243 Filter, Screw-in, 52mm, ND-4X AC2244 Filter, Screw-in, 52mm, ND-8X	13.50
AGZZ44 Filter, Sciew-III, Szillilli, ND-oA	13.50
Nikon Polarizing Filters — used to obtain polarized light correction.	ROOM.
- ACR2250 Polarizing Filter, screw in, rotating mount, 52mm for all F lenses	10
from 21mm through 135mm and 200mm	21.00
Lens & Body Caps	

ACR587 Camera Body Cap for Automatic Reflex .....

ACR607 Rear Lens Cap, for all F lenses except 8mm, 21mm .....

REI	LEX ACCESSORIES—Continued	Retail List WITH EXCISE TAX WHEN APPLICABLE	Retolf List WITH EXCISE TAX WHERE APPLICABLE		Retail List WITH EXCISI TAX WHEN APPLICABLE
AC	Rear Lens Cap, 8mm; 21mm. Reflex	2.65	BFP2631	Adapter Tube for Bellows Attachment Model 2, for use with shomount 135mm. f4.0	. 9.50
	R617 Front Lens Cap, for 85-250mm, 200-600mm Zooms		BFP2632	Slide Copy Attachment 1:1, for Bellows Attachment Model 2; for	
	613 Front Lens Cap, fits 180, 250, 350mm		BFP2637	35mm. slides and roll film	
	614 Front Lens Cap, for 250mm		AC2730	MB Adapter Tube for 55mm Micro Nikkor	
AUI	615 Front Lens Cap, for 500mm short mount	10.50	AC2731	Close-up Attach. Lens No. 2; 52mm	
NO A THE	REFLEX GADGET BAGS	TTGROWN STORY	RC2750	Reprocopy Outfit PFC, for Automatic Reflex. Consists of copy hear bracket, 5.8mm. extension tube, 2 piece chrome upright and fitte	d, ed
DC.XX LB DO FA TIL	Leather Mini Compartment Case F B 1 — Holds Nikon F with not lens, meter, lenshood, BC5 flashgun, flash coupler, 3 filters, film	28.50	RC2751	carrying case which serves as the working platform	ot
UU.	191 Fitted Foam Rubber Compartment Case Model A — Holds camera normal lens, 3 accessory lenses, exposure meter, miscellaneous ac	WITH	FT0700	supplied with baseboard which serves as working platform	
	sories. Case is made of leather. Includes strap	55.00	ET2720 MF810	Extension Tube E, Semi-Automatic	
CC	192 Fitted Compartment Case Model FB4—Holds camera with normal 1 1 accessory lens, exposure meter, electric motor drive, battery	case	2.75	scope adapter tube, interchangeable ground glass, Model C, 3 col trast filters	n-
cc	and miscellaneous accessories. Case is made of leather. Includes s		MF815	Microscope Adapter Outfit for Nikkorex F	. 30.00
U.	193 Fitted Compartment Case Model FB3—Holds camera with normal 2 wide angle lenses, 1 telephoto lens, exposure meter, boo waist level finder, filters and miscellaneous accessories. Casi	ster.	MF804	Microflex Attachment, complete with ground glass screen, magnifie for Nikon F Reflex	
I ENS C	made of leather. Includes strap	83.50	TSP752	Telescope Adapter Outfit, for Automatic Reflex. Consists of adapte tube, focusing screen with condenser and fresnel lens, 6 filters, a	110000000000000000000000000000000000000
		85333A	TSP755	in a leather case	. 55.00 . 41.50
	35 Lens case for 21mm f4.0; leather		131 700	relescope Adapter outlit for Mikkorex F	41.30
CC4	40 Lens case for 28mm f3.5; 35mm f2.8; 50mm f1.4; 58mm f1.4; leather		MISCELLANE	EOUS	
CC				The property of the state of the property of the state of	
CC4			‡ACR2900	<b>Eyepiece Correction lenses,</b> for Automatic Reflex—Spherical corretion only; $-5$ , $-4$ , $-3$ , $-2$ , $-1.5$ ; $+3.0$ , $+2.0$ , $+1.0$ ,	c- 3.75
CC			AC630	Leather Neckstrap	
CC4		32.50	AC654	Instruction book, Auto Reflex	50
CC4		10.50	AC660	Cable release, camera, with lock	3.95
	146 Lens case for 28mm to 58mm lenses; plastic		AC655	Instruction Book, F Photomic	
CC	47 Lens case for 105mm, 135mm lenses; plastic		AC656	Instruction Book, Nikkorex 'F'	50
CC4			AC47	Adapter for Coupling Cable, Nikkorex F	
MACRO	& MICRO COPY EQUIPMENT — for Automatic Reflex	26.1 Million Pa		‡ specify power when ordering	
	Bellows Focusing Attachment Model 2 for Auto Reflex  Macro Adapter, for Bellows Attachment Model 2, for 50mm. f2.0			tors states means to be a feel feel feel feel feel feel feel f	