Compact all-weather
35 by Nikon even
takes pictures
under water
without a housing
NIKONOS

hermetically sealed • waterproof and dustproof • resists salt-water corrosion, mildew and fungus
virtually indestructible

Nikonos takes pictures where you'd never risk using another camera: rain, snow, tropical humidity, arctic cold and desert dust—even under water, 160 feet below, without a housing. After it has gone through the worst the elements can offer, a rinse under a faucet makes it shine like new.

Compact, easy to use and fast-handling as any fine 35, the Nikonos is great for fine-weather pictures, too. A superb, interchangeable Nikkor lens heads the list of features, and a full complement of accessories fits it for a multitude of applications.

Nikonos is supplied with choice of two Nikkor lenses: 35mm f2.5, for use in or out of water; and 28mm f3.5, specially designed for underwater photography only. Both lenses are also available as accessories.

FEATURES



- 1. Die-cast metal body covered with cross-ridged, nonslip vinyl. All exposed parts are corrosion resistant; all internal parts anti-corrosion treated.
- 2. Interchangeable Nikkor lenses standard 35mm f2.5 (focuses to 33"; picture angle under water 46°, out of water 62°), and special 28mm f3.5 for underwater use only (focuses to 24"; picture angle 59°). Each lens is protected by a sealed optical glass window.
- **3. Rapid one-lever operation** Single, short sweep of lever advances film and cocks shutter; then the same lever serves for making the exposure.
- 4. Automatic-depth-of-field indicator Setting lens aperture automatically masks off effective depth-of-field.


- **5. Luminous-frame finder** shows field of 35mm lens. Has parallax markers for closeups. Accessory open-frame finder is used with 28mm lens.
- **6. Shutter speed selector** controls focal plane shutter speeds from 1/30 to 1/500th second, plus B. Shutter is automatically synch'd for flash bulbs and electronic flash.

plus 7. extra-large knurled focusing knob; 8. extra-large knurled aperture control knob; 9. hinged neckstrap lugs (also used for opening camera); 10. pull-up rewind knob; 11. accessory shoe; 12. safety lock prevents accidental exposure; auto-reset exposure counter, and tripod socket with flash contact (in base).

ACCESSORIES



OPEN-FRAME VIEWFINDER Fits camera accessory shoe. Invaluable for underwater shooting with camera held at distance from face; also for following action out of water. 2 types available: for 35mm and for 28mm lens.



UNDERWATER B-C FLASH UNIT Completely sealed, waterproof and corrosion resistant. Accepts standard bayonet-base focal plane flash bulbs. Battery capacitor circuit. Built-in vinyl-clad synch cord. FLASH UNIT ADAPTER Permits use of conventional electronic and flashbulb units out of water.



UNDERWATER EXPOSURE METER water-tight, pressure-proof plastic housing with long nylon cord, containing removable Sekonic L-86 meter. L-86 is calibrated for film speeds ASA 6 to 12000; Exposure Values EV 2 to 19; apertures f1.0 to f32; shutter speeds 8 seconds to 1/2000th. Housing is also available without meter.



LENS HOOD/FILTER HOLDER Screws into lens mount. Accepts 52mm screw-in filters.



OPTICAL GLASS FILTERS 52mm screw-in; yellow, green, orange, red, u.v., haze, skylite, 80B, 80C, 81A, 82A, 85, 85B, ND-4x and ND-8x. Filters fit lens hood only.



LEATHER CARRYING CASE Soft, water-repellent, treated to resist mildew and fungus. Non-corroding zipper.