



The Konica Autowinder F provides tremendous flexibility and versatility to the Konica FC-1 Systems. Imagine shooting 36 exposures in 24 seconds flat or couple it with the Konica Interval Timer and let it take one exposure each hour for 36 consecutive hours. The Konica Autowinder F also couples to the unique automatic film loading system of the Konica FC-1.

Key Features

- Provides fully automatic loading for the Konica FC-1 System. Drop the film cassette into the Konica FC-1, extend the leader and close the back. The Konica Autowinder will automatically advance the film to frame No. 1.
- Compact and lightweight. Only 5.6" long, 1.4" high and weighing just 61/2 ounces.
- Provides single frame or continuous film advance for shooting at 1.5 frames per second.
- Can be used with all shutter speeds, from 2 seconds to 1/1000 second.
- Red LED indicator blinks each time the film is automatically advanced and remains on to indicate the end of roll.

Konica

for Konica FC-1 system

Autowinder F

Cat. No. 705-363

- Sealed camera coupling mechanism does not require special dust cover.
- · Powered by just four (4) AA penlight batteries.
- Attaches to camera by large knurled mounted knob.
- · Convenient on/off power switch.
- Standard tripod socket provided.



Technical Specifications

TypeDesigned exclusively for use with Konica FC	-1
Frame Speed1.5 frames per second	nd
Shutter Speed Coupling RangeAll shutter spee 2 seconds to 1/1000 secon	ds d.
Operation IndicatorLED lights when fill is being advance	m d.
End of Film Indicator LED remains on indicate end of ro	

Film Loading Automatically advances film to frame No. 1.	Film
Power SourceFour (4) AA 1.5V Alkaline or Rechargeable Nicad penlight batteries.	Powe
Winding Capacity Approximately 40 rolls of 36 exposures with Alkaline batteries.	Wind
Dimensions	Dime
Weight	Weigl

Specifications subject to change without notice