

# Daylight Developing Outfit

for use with the

## Compass Camera

Specially manufactured for

R. CLIFTON LTD., 51 Eden Street, KINGSTON-ON-THAMES

---

### INSTRUCTIONS FOR USE

THE DAYLIGHT DEVELOPING OUTFIT consists of three separate articles—Miniature tank, Developer and Fixer Bottles (two). Note: The two bottles are distinguishable quite easily, the developer having one ring and the fixer two rings.

First, fill your developer bottle with the solution which you decide to use and screw the cap home to prevent leakage, and then see to the fixer bottle in the same way. Now your outfit is ready to use wherever you are, but should you be away from home, a bottle of water and a small receptacle will be required for washing off.

Remove the cap from the developer bottle—that is the one with one ring—and screw the bottle into the tank. Release the clip from the tank back, insert the single exposure unit, close the back, and whilst holding same finger tight, pull up the envelope slide, then return the clip to the locked position. (Note that the loading of the tank is done in much the same way as loading the camera).

Now move the complete developing unit about, to ensure that the film is completely covered with the solution, and when the required development time has been given, remove the developer bottle, and replace this with the fixer bottle (two rings), and ensure that there has been sufficient movement to allow of the film being properly covered. The fixing complete, remove the bottle, open the tank and wash the negative in the usual way.

DO NOT LEAVE YOUR SOLUTIONS TOO LONG AFTER USE IN THE BOTTLES, BUT KEEP THEM WASHED OUT. ALWAYS WASH OUT THE TANK AFTER USE.