HASSELBLAD® 553ELX





If your field of photography includes critical studio work as well as handheld action photography, we have the ideal camera for you – the Hasselblad 553ELX.

A built-in motor drive advances the film after every shot, so you can keep your eye in the finder and have more time to create exactly the image you want. The built-in dedicated flash metering system produces accurate flash exposures automatically, dedicated flash metering system produces accurate flash exposures automatically, so you can concentrate on your subject instead of changing lens apertures. As on all Hasselblads everything in the camera and the lens is built to perfection, as on all Hasselblads everything in the camera on a  $2.1/4 \times 2.1/4$ " negative or to assure the best image sharpness and contrast on a  $2.1/4 \times 2.1/4$ " negative or transparency (3.1/2 times larger than a 35 mm frame). With the 553ELX these

ransparency (3 1/2 times larger than a 35 mm frame). With the 333ELA these high quality images can be produced in the simplest and most professional fashion.





The 553ELX motor is an intergrated part of the camera, permanently linked to the camera mechanism for the most reliable operation.


The motor advances the film automatically after each exposure, whether you take single pictures or sequences, working from behind the camera or with a remote control.

The dedicated flash system used on the 553ELX ensures extremely accurate automatic flash exposures, at close or long range, with direct, bounced or reflected flash, and even using close-up accessories. The flash ready light and exposure signal indicating sufficient light are both visible in the camera viewfinder, greatly simplifying the overall use of flash lighting.

The 553ELX uses Zeiss CF series lenses with built-in leaf shutters, allowing flash pictures to be taken at all shutter speeds up to 1/500 s, for complete control over lighting ratios in flash fill work and the elimination of "ghost" effects in action shots.

Your image creation possibilities are improved considerably with the new Acute-Matte<sup>1)</sup> focusing screen. The bright corner-to-corner image shows minute details for the most accurate focusing even in dim light, further ensuring your photographs the benefits of the renowned Hasselblad image quality, frame after frame.


<sup>1)</sup> Acute-Matte designed by MINOLTA



**Integrated motor drive.** Single pictures or sequences, with or without the mirror locked up and with remote control.




**Power for 4,000 exposures.** Five standard type AA alkaline batteries supply power for 4,000 exposures. A battery check indicates when it is time to replace.



Bright viewfinder image. The Acute-Matte<sup>1)</sup> focusing screen provides an extremely bright, corner-to-corner image for quick and accurate focusing even in dim light.


"Acute-Matte designed by MINOLTA



**Automatic dedicated flash.** The built-in flash metering system measures the light through the lens (TTL) and off the film plane (OTF) for accurate exposures.



**The Hasselblad System.** The 553ELX works with all existing CF lenses, film magazines, viewfinders and most other accessories in the Hasselblad system.



**Built-in security.** The 553ELX is designed for heavy professional work. Its reliability is assured by precision workmanship and meticulous quality control.

Single lens reflex with built-in motor drive and interchangeable film magazines, viewfinders and 2 1/4  $\times$  2 1/4" (6  $\times$  6 cm) and 1 5/8  $\times$  1 5/8" (4  $\times$  4 cm) superslides with other film magazines. 2 1/4  $\times$  1 5/8" (6  $\times$  4.5 cm) and 1 5/8  $\times$  1 5/8" (4  $\times$  4 cm) superslides with other film magazines. Hasselblad 553ELX camera specifications: 120 rollfilm 220 rollfilm; 70 mm long rolls, sheet film and Polaroid film with other film magazines. Camera shell and motor housing are made of one-piece aluminium and magnesium alloys Camera type Automatic, motorized film advance and shutter cocking with function modes for single exposures, or sequences.

Exposure rate of approx 1 2 frames Remote release capability. Film format Sequences. Exposure rate of approx. 1.2 framesis. Remote release capability.

Five standard 1.5 V AA alkaline or 1.2 V rechargeable NiCd batteries. Over 4,000 exposures with a get of alkaline batteries. Film choices Fast folding, all steel focusing hood with 5× magnifying lens interchangeable to match the photographer's evesight. Finder instantly interchangeable with 45° or 90° prism finders. Camera body Fast folding, all steel focusing hood with 5× magnifying lens interchangeable to match the photographer's eyesight. Finder instantly interchangeable with 45° or 90° prism finders. Hasselblad Acute-Matte Screen, a proven and highly acclaimed Minolta design, is interchangeable with other screens with micro prism. split image rangefinder or plain glass Film advance with other screens with micro prism, sput image range jinder or plain guss.

With other screens with micro prism, sput image range jinder or plain guss.

Scalable dedication with adapter for flash dedication with adapter for flash to 1000 ISO. Flash dedication with adapter for flash center weighted TTLIOTF metering for films 16 to 1000 ISO. Flash dedication with adapter for flash center weighted TTLIOTF metering for films 16 to 1000 ISO. Flash dedication with adapter for flash center weighted TTLIOTF metering for films 16 to 1000 ISO. Flash dedication with adapter for flash center weighted TTLIOTF metering for films 16 to 1000 ISO. Flash dedication with adapter for flash center weighted TTLIOTF metering for films 16 to 1000 ISO. Flash dedication with adapter for flash center weighted TTLIOTF metering for films 16 to 1000 ISO. Flash dedication with adapter for measurement. Center weighted 11LIU1F metering for Jims 10 to 1000 ISU. Flash aeaication with adapter for Jiasi systems SCA 300 or SCA 500. \$\infty\$40 mm area in the centre of the film surface used for measurement. systems SCA 300 or SCA 300. V40 mm area in the centre of the film surface usea for measurement.

14 interchangeable Carl Zeiss CF fixed focal length lenses from 30 mm fisheye to 500 mm telephoto

14 interchangeable Carl Zeiss CF fixed focal length lenses from 30 mm fisheye to 500 mm telephoto

14 interchangeable Carl Zeiss CF fixed focal length lenses from 30 mm fisheye to 500 mm telephoto

15 The fixed focal length lenses from 30 mm fisheye to 500 mm telephoto

16 The fixed focal length lenses from 30 mm fisheye to 500 mm telephoto

17 The fixed focal length lenses from 30 mm fisheye to 500 mm telephoto

18 The fixed focal length lenses from 30 mm fisheye to 500 mm telephoto

19 The fixed focal length lenses from 30 mm fisheye to 500 mm telephoto

19 The fixed focal length lenses from 30 mm fisheye to 500 mm telephoto

10 The fixed focal length lenses from 30 mm fisheye to 500 mm telephoto

10 The fixed focal length lenses from 30 mm fisheye to 500 mm fisheye to 500 mm fisheye to 500 mm fisheye to 500 mm fisheye focal length lenses from 30 mm fisheye to 500 mm fisheye focal length lenses from 30 mm fisheye focal length lenses from Battery capacity Viewfinder and a Schneider 140-280 mm Zoom. Zeiss Mutar  $2\times T^*$  Teleconverter. Leaf shutters in lenses for flash synchronization at all shutter speeds up to 1/500 second. Focusing The 553ELX takes all CF and C lenses, all film magazines, viewfinders, and focusing screens made for the 500 series camera models. screen Flash control Jut the 300 series camera models.

Camera body with 80 mm Planar CF lens and film magazine A12: 7" long, 4" wide and 5 7/8" high  $(180 \times 100 \times 150 \text{ mm})$ Lenses Camera body only: 2 lbs 11 ozs (1240g). The camera body with 80 mm Planar CF lens and film magazine A12. 4 lbs 11 ozs (2130 $\sigma$ ) magazine A12: 4 108 11 028 (21308).

The Camera body (chrome model, product nr. 10067 or black model, product no. 10221), comes with release plate and FK30 release cord Shutter The Camera body (chrome model, product nr. 1000/ or black model, product no. 10221), cold the Camera body (chrome model, product nr. 1000/ or black model, product no. 10221), cold the Camera body (chrome model, product nr. 1000/ or black model, product no. 10221), cold the Camera body (chrome model, product nr. 1000/ or black model, product no. 10221), cold the Camera body (chrome model, product nr. 1000/ or black model, product no. 10221), cold the Camera body (chrome model, product nr. 1000/ or black model, product no. 10221), cold the Camera body (chrome model, product nr. 1000/ or black model, product no. 10221), cold the Camera body (chrome model, product nr. 1000/ or black model, product nr. 1000/ or blac System compatibility For comprehensive information on accessories please refer to the Hasselblad Product catalog. **Dimensions** Weight Camera finish

## Victor Hasselblad Aktiebolag

Box 220, S-401 23 Göteborg, Sweden