CRYSTAL CONTROLLED MOTOR BATTERY AND CHARGER

FOR BNC, NC AND MARK II OR S35R CAMERAS

Ginema Products has developed this special battery and charger unit primarily for use with their crystal controlled motors for the NC, BNC, and Mark II or S35R cameras . . . The total package weighs only 32 lbs., yet it provides a full day's running for a BNC under normal operating conditions.

FEATURES:

C

- Large Capacity
 Zero Maintenance Sealed
- Cells
- Reliable, Dependable and Simple Lead-Acid Performance
- Color Coded Meter and Feed Through Sync Pulse
 Output
- Air Transportable in any Orientation or Condition of Change
- Rugged Construction
- Low Cost
- Modular Construction
- Extremely Portable

TECHNICAL SPECIFICATIONS:

 Nonifal rating — 12 amp-hrs @ 30 v.d.c. (Note: At typical BNC current drain of 4 to 5 amps, capacity de-rates to approximately 9 A-H — about 10,000 ft. of film.)
 Weight — 32 lbs.

Cell life — approximately 500 cycles for average charge/discharge cycle. Pin connections — 8 pin (P8-13) #1 Sync. signal;

Pin connections — 8 pin (P8-13) #1 Sync. signal; #2 sync. shield; 5 B - ; 7 B + 3 pin (XLR) #2 sync. signal; #3 sync shield

CHARGER — Charge profile, constant current (2 amp.) to rated full charge cell voltage, then constant voltage with tapered current to indicate full charge current; then trickle for unlimited period. Operation: 50/60 Hz with choice of 100, 120, 200, 240 v.a.c. input.

Resettable $2\frac{1}{2}$ amp circuit breaker.

PRICES:

BATTERY		\$375.00
CHARGER		\$200.00
REPLACEMENT CELLS	set	\$250.00
Free factory installation	available	

