



The Professionals' Choice



Gitzo make two styles of tripod - Standard or Performance - each offering very distinctive benefits.



Standard style tripods, have one fixed position leg spread of 24° which ensures the center column is always vertical at a given leg extension and is rock steady.



Performance style tripods, are fitted with sliding stops, which enable the legs to be individually set at different angles, providing more flexibility including very low angle shots. There are two set angles on the Series 0; 1, 2 and 3 Studex of 24° and 55°, and three set angles of 24°, 55° and 80° on the Inter Pro Studex Series 3, plus 4 and 5 series.



par, excellence

Quality & Precision Gitzo tripods are superbly engineered to withstand the most robust handling. High strength lightweight aluminum or carbon fiber tubes resist twist and stress to provide absolute stability. Fine-tolerance telescopic legs ensure smooth silent gliding action every time. All tripods are easily assembled and maintained.

**Twist Lock Knobs** All telescopic movements, including adjustment to the center column, glide effortlessly into position. The cushioned locking rings and wing locks, ensure no slippage whatsoever, yet are all released with great ease. All tripods are include reversible 3/8" and 1/4" mounting screw.



re cc ww cc ac





G1560 MonoTrek®

**Smooth Control** A wide choice of interchangeable heads, for both photographic and video shoots, extends Gitzo tripod's versatility. Three axis and ball heads plus the Fluid Video Head are precision engineered for superb fingertip control. Gitzo heads include a <sup>1</sup>/<sub>4</sub>" mounting screw as standard. See page 17 for optional <sup>3</sup>/<sub>8</sub>" mounting screw.



G1275M Magnesium Ball Head.



G1572 Rationnelle Three Way Head.



G1370 Rationnelle Low Profile Head.



G1380 Fluid Video Head.

### KEY TO SYMBOLS

Column Type

Max Height

Min Height

Closed Height

Weight lbs

Max Load lbs

Plate Size

Lateral Tilt

Vertical Tilt
Pan

Tripod Series

Top Tube

ZZZ Arm Type

Center Column
Sections

A Telescopic Leg Sections

**▶** Travel

CONTENTS Introduction 2-3 Tripods 4-9 Monopods 10 Center Columns 11 Lateral Arms 11 Gitzo Heads 12-16 Heads & Tripod Guide 16 Accessories 17 Fluid Video Head 18 Fishpoles 19 Levelling Bases & Bags 19 **Product Index** 

### Carbon Fiber Tripods

# Mountaineer

### G1228 Series 2 - Photographic

Top leg Ø:- 1 1/8" Loads up to:- 13 1/2 lbs Matching head:- Series 2

**Application:-** The G1228 Mountaineer Tripod is manufactured from CARBON FIBER and is 25% lighter than the equivalent aluminum tripod while maintaining the robustness and rigidity expected from Gitzo.

The G1228 is a performance model which enables the legs to be set individually at either 24° or  $60^{\circ}$  for low angle shots. The tripod features a Rapid center column and is suitable for 35mm,  $6 \times 4.5$  and light  $6 \times 6$  cameras.

Its compact size, remarkable low weight and robustness make it an ideal choice for outdoor wildlife and nature photographers, while being

equally advantageous for wedding or studio applications. The G1228 sets new standards for photographic tripods!

# Mountaineer


### G1338 Series 3 - Video

Top leg Ø:- 11/4" Loads up to:- 261/2 lbs Matching head:- Video


Application:- The G1338 Mountaineer Video Tripod with 75mm bowl for professional video cameras is manufactured from CARBON FIBER and is 30% lighter than the equivalent aluminum tripod while maintaining the robustness and rigidity expected from Gitzo.

No need for mid-level or floor spreader, the G1338 is a performance model which enables the legs to be set individually at either 24°, 55° or 80° for low angle shots. Fitted with rubber feet and retractable spiked tips, this is the ideal combination for the Gitzo G1380 Fluid Head for on the move videography.





G1228 Mountaineer.



# Mountaineer

### G1348 Series 3 - Photographic/Video

Top leg Ø:- 11/4" Loads up to:- 261/2lbs Matching head:- Series 3 + Video

Application:- The G1348 Mountaineer Tripod is the base for either a photographic tripod with sliding column (G1349) or video tripod without center column (G1348). With optional 75mm (G1422) or 100mm (G1424) bowl interface the G1348 is conveniently converted into a professional cine/video tripod.

The tripod is manufactured from CARBON FIBER and is 30% lighter than the equivalent aluminum tripods without compromise on strength.

The G1348 is a performance model which enables the legs to be set individually at either 24°, 55° or 80° for low angle shots.

for wedding and portrait photographers.

### G1548 Series 5 - Photographic/Video

Top leg Ø:- 15/8" Loads up to:- 39 1/2 lbs Matching head:- Series 5

Application:- The G1548 Mountaineer Tripod is the base for either a photographic tripod with sliding column (G527) or geared (G528) center column. The G1548 is conveniently converted into a professional cine/video tripod with optional 75mm (G1422) or 100mm (G1424) bowl interface.

The tripod is manufactured from CARBON FIBER and is 30% lighter than the equivalent aluminum tripods without compromise on strength.

The G1548 is a performance model which enables the legs to be set individually at





G1349 Mountaineer.

Optional Extras

G1422 Video Interface Bowl 75mm. G1424 Video Interface Bowl 100mm.
 G336 Standard Geared column. G338 Compact Geared Column.
 Column Type: O=No column R=Rapid G=Geared.



G1422 Video Interface Bowl 75mm. G1424 Video Interface Bowl 100mm. G527 Standard Geared column. G528 Compact Geared Column. Column Type: O=No column R=Rapid G=Geared.

# Classic Tripods

# Table

### Series 00

Top leg  $\varnothing$ :- 5/8" Loads up to:-  $6^{1/2}$  lbs Matching head:- Series 0

Application:- One of the most popular table and/or mini tripods offering maximum rigidity for compact cameras and specialist applications. Features effortless double lift center column and can be used as a firm wall brace. Extremely portable, this model fits into the smallest of accessory bags!

# **Veekend**

### Series 0

Top leg Ø:- 3/4" Loads up to:- 51/2 lbs Matching head:- Series 0

Application:- A compact yet sturdy tripod for mounting lightweight 35mm and small camcorders. Choice of fixed (STANDARD) or variable (PERFORMANCE) leg spreads. Makes an ideal travelling companion. Especially useful for macro-photography applications.






G0011 Table Tripod.



G01 Standard and G026 Compact Performance.





# Sport

### Series 1

Top leg Ø:- 7/8" Loads up to:- 10lbs Matching head:- Series 1

**Application:-** Suitable for all 35mm cameras and lightweight video recorders, these tripods fall into two categories. STANDARD models, with 24° leg spread and single lift center column or PERFORMANCE models, with 2 position leg spread and a double lift reversible center column or geared column. The Performance Tatalux is ideal for the backpacker.

## versatile



G126 Performance Tatalux and G101 Standard.

### Series 2

Top leg Ø:- 11/8" Loads up to:- 131/4 lbs Matching head:- Series 2

**Application:-** 35mm, 6 x 4.5 and 6 x 6 cameras... this versatile fixed (STANDARD) or variable (PERFORMANCE) leg spread range with rapid or geared center column includes the Monotripod which has one removable leg to form a monopod. Popular among sports and wedding photographers.



G1222 Monotripod.



G220 Performance and G212 Performance.

		2		2		1	1
G10	1 G106 G	120	G1	26	G11	2	G118
Ref	Model	***	$\Lambda$	个	i		max
G101	Standard	R	541/2	173/4	191/2	3	10
G106	Standard Tatalux	R	521/8	125/8	135/8	23/4	10
G120	Performance	R	581/4	113/8	205/8	31/4	10
G126	Performance Tatalux	R	583/4	12	15	3	10
G112	Performance	G	561/2	113/4	211/4	33/4	10
G118	Geared 1 Short Colum	n G	511/8	11	215/8	31/2	10
Colum	n Type: O=No colun	n R=	Rapid	G=G	eared		

	2	2	12		2	1		1	1
G201	G220 (	G1222	G224	G2:	26	G212	G2	18	G228
Ref	Model		////	$\overline{\mathbf{A}}$	个	ı		max	
G201	Standard		R	571/2	181/4	193/4	4	131/4	
G220	Performance	9	R	581/4	123/4	211/4	41/4	131/4	
G1222	Monotripod		R	731/8	131/2	24	51/4	131/4	
G224	Industrial Pe	rformance	R	733/4	145/8	25	5	131/4	
G226	Compact Pe	rformance	R	581/2	103/4	173/4	41/4	131/4	
G212	Performance		G	691/2	15	251/2	51/2	131/4	
G218	Geared 2 Sh	ort Colum	n G	633/4	15	26	51/2	131/4	
G228	Performance		G	64	12	181/2	41/2	131/4	
Columi	n Type: O=	No colum	n R=	Rapid	G=0	Geared			

## Classic Tripods

# Studex

### Series 3

Top leg Ø:- 11/4" Loads up to:- 193/4 lbs Matching head:- Series 3

**Application:-** All models have 2 independent leg spread angles giving easy access to any camera position. Studex tripods are available with rapid reversible or geared center columns. The range includes the unique Monotripod which has one removable leg to form a monopod. Supports all medium and light format 4 x 5 cameras as well as video cameras.

G1322 Monotripod.

# nter Pro Studex


### Series 3


Top leg Ø:- 1<sup>1</sup>/<sub>4</sub>" Loads up to:- 22lbs Matching head:- Series 3 + Video

Application:- For photographers who will settle for nothing less than a Studex tripod, but require extra stability for loads up to 22lbs. Incorporates all the features of the Pro Range with interchangeable center columns, wing lock-offs and 3 position leg spread. The G340 and G345 are perfect supports for professional video cameras using the optional extra interface bowls (G1422 = 75mm or G1424 = 100mm).

G346 Compact Performance and G342 Performance.

G326 Compact Performance and G312 Performance.





# **Pro Studex**

### Series 4

Top leg Ø:- 11/2" Loads up to:- 26lbs Matching head:- Series 4

Application:- Cameras up to 8 x 10 and Professional Video. The Pro Studex series offers durability and versatility with a choice of six models, all with 3 position leg spread, interchangeable rapid (sliding) or geared columns plus special short columns for extra low shots. Ideal for commercial/industrial photographers. The G410 is the perfect tripod for on the move professional videographers using the optional interface bowls (G1422 = 75mm or G1424 = 100mm).



G416 Compact Performance and G412 Performance.

### Series 5

Top leg Ø:- 15/8" Loads up to:- 44lbs Matching head:- Series 5

Application:- Tele Studex performance models similiar to the Pro Studex but with larger diameter legs for heavy video, TV and 8 x 10 cameras. Ideal for ENG users. The G505 with optional interface bowl (G1424 = 100mm) and 3 position leg spread is ideal for professional videographers.



G506 Compact Performance and G509 Giant Performance.

3			3 H			1	
10	G411 G4	12	G4	115	G41	6	G417
Ref	Model	<i>////</i>	$\Lambda$	个	Ĩ		max
G410	Performance	0	641/8	193/8	291/2	81/2	26
G411	Performance	R	781/2	211/2	311/4	93/4	22
G412	? Performance	G	75 <sup>7</sup> /8	211/2	311/4	111/2	26
G415	Compact, Performance	0	451/2	13	191/4	63/4	26
G416	Compact Performance	R	59 <sup>7</sup> /8	143/4	21	8	22
G417	Compact Performance	G	571/4	143/4	21	93/4	26

			1		<b>A</b>		
G500 C	G501 G502 G504	G508	G509	G505	G506	G507	G515
Ref	Model		$\Lambda$	个	Ĩ		max
G500	Performance	0	631/4	191/4	281/2	93/4	33
G501	Performance	R	761/2	211/2	303/4	103/4	22
G502	Performance	G	74	211/2	303/4	121/2	33
G504	Giant Performance	0	98	20	311/2	121/4	33
G508	Giant Performance	R	1111/4	221/4	333/4	131/4	22
G509	Giant Performance	G	1083/4	221/4	333/4	151/4	33
G505	Compact Performance	0	583/8	16 <sup>1</sup> / <sub>4</sub>	231/4	9	33
G506	Compact Performance	R	713/4	181/2	251/2	101/4	22
G507	Compact Performance	G	691/8	18 <sup>1</sup> / <sub>2</sub>	251/2	12	33
G515	Performance Industrial	0	473/4	213/4	321/2	81/2	44
Calum	Tuna. O Na saluman	D D:-	0 0				

Gitzo Monopods set the standards only others can aspire to. This range of compact, lightweight, corrosion resistant Monopods includes a model for every application with 3, 4, 5 and 6 section lifts with head platform and interchangeable 3/8" or 1/4" camera mounting screws. All models include a comfortable wrist strap.

The G1565 is fitted with an independent tilting head and a two section shoulder chest brace. This is adjustable for both length and angle. The heads have a 1/4" mounting

No sporting or similar live action coverage would be complete without a Gitzo Monopod!



G1565 Monopod.

G1564 Monopod.

G566 Monopod.

G1568 Mountaineer.

G1560 MonoTrek®.

Gitzopod - a unique combination of Monopod, Chestpod, Emergency tripod and Tablepod.

Weighing just 2<sup>1</sup>/<sub>4</sub> lbs and suitable for cameras up to 11lbs, Gitzopod features a fully adjustable telescopic shoulder brace which is independent of the panoramic tilting head.

Supplied together with a neck harness for extra stability. The harness also frees both hands for operating the camera.



G558 Gitzopod.

### MonoTrek®


The new Gitzo MonoTrek® is an ergonomically designed lightweight monopod/walking stick, which is ideal for long distance walkers and back-packers. It is manufactured with ultra-light strength (FSS) aluminum alloy with triple elastic binding capacity. Comes complete with an integrated ball head for photographic cameras and camcorders up to 4<sup>1</sup>/<sub>2</sub> lbs in weight. It has telescopic height adjustment, steel spiked foot and all




Integral Ball Head with 1/4" camera mounting screw.



MonoTrek® can be used on the softground or snow using the allweather shoe. The detachable rubber shoe slides simply onto the end of the MonoTrek®



Ref	Model	0		T	<b>[</b> ]3	max
G1560	MonoTrek®	3/4	633/4	303/4	7/8	41/2
G1561	Sport	7/8	611/8	243/4	11/4	63/4
G1563	Reporter	11/8	64	211/4	11/2	83/4
G1563L	Reporter	11/8	803/4	223/8	11/2	83/4
G1564	Studex	11/2	621/2	215/8	13/4	171/2
G1564L	Studex	11/4	781/2	223/8	2	171/2
G1565	Studex with brace	11/2	623/4	21 <sup>7</sup> /8	2	171/2
G566	Mini-Studex	11/2	533/4	141/2	11/2	11
G558	Gitzopod	11/2	601/4	261/2	21/4	11
G1568	Mountaineer	11/8	651/4	215/8		83/4



### Center Columns

Tripods in the Series 00 to 3 come complete with Rapid (Sliding) or Geared center columns.

The Inter Pro Studex, Pro Studex and Tele Studex ranges have interchangeable columns available as Rapid (Sliding) reversible or Geared columns for superfine control.

Very short columns are also available for very low angle work.
Rapid column extensions are available for Series
0 - 1 - 2 - 3 for extra height.



Left to right, G526, G335C and G525 center columns.

### Lateral Arms

Lateral arms enable cameras to be positioned above or below the tripod apex in positions which might otherwise be obstructed by the tripod legs.

Both Rapid (Sliding) and Geared versions are available.

For optimum rigidity, make sure to select a lateral arm with the same diameter as the tripod's outer section.





G541 Graduated Right Angle Bracket.



G540 Right Angle Bracket.




G349 Circular camera platform. (Tripod series 3). G449 Circular camera platform. (Tripod series 4+5).



Equally as important as the Gitzo tripods in providing rock solid support, the Gitzo range of heads are carefully engineered to position the camera precisely in the required shooting position with the minimum of fuss for optimum results.

There are three specific ranges of heads designed to cover all photographic possibilities, offering unlimited support and flexibility.

Each head is carefully crafted to take specific pay loads to work in combination with the equivalent Gitzo tripod or can be fitted to most manufacturer's tripods. Gitzo heads cover all angles!



### **Ball Heads**

There are nine Ball Heads from which to choose including fixed or quick release camera plate versions, plus the innovative, ultra lightweight G1275M Magnesium Ball Head.

(Right) G1276 Ball Head with Quick Release Plate.



### Rationnelle Low Profile Heads

Low Profile Heads are intended for heavy, medium and large format cameras

Photographers are able to use larger cameras comfortably, making full use of the benefits of vertical and lateral tilt plus 360° panning.

(Right) G1270 Low Profile Head illustrating tilt, pan and side to side control locks.





### Quick Release Plate

The Gitzo Quick Release system has been introduced on some of the Rationnelle and Ball Heads. Efficient use of time is important in photography and so the Quick Release plates provide an easy and convenient way of mounting a camera.

A standard plate size is supplied with the relevant models. Optional Long plates are also available, (see page 17).



To insert Quick Release plate press down and plate snaps into position automatically.



To release the Quick Plate, squeeze secondary safety lock and push lever forward at the same time.

## precision engineering

### Rationnelle Three Way Heads

The range of Three Way Heads allow photographers the freedom of movement to shoot in all three axis, pan, tilt and side to side, irrespective of size and type of equipment used.

An important feature on these heads is the forward and backward tilt with friction counter-balance and left or right hand operation.

(Right) G1372 Rationnelle Three Way Head.





Ball Heads

Exceptionally smooth rotation, positive locking and rapid camera mounting are all features common to the exclusive Gitzo-designed range of ball heads.

The graduated base, with independent locking knobs (except on G1175) permits perfect panoramic photography. The design of the panoramic base permits the ball heads to be used for table top or near ground level work without the use of a tripod.

All Gitzo ball heads incorporate (except G075, G1175) have an increased operational range with the introduction of a rotating central socket which allows unrestricted movement.

A Quick Release plate with secondary safety lock and the option of a Long Plate provide additional flexibility on Model G1276, G1376 and G1576; the camera can be removed from the head within seconds and fitted back on the head as easily.

1/4" mounting screw is included, but 3/8" mounting screw is also available (see page 17).



G075 Ball Head.



G1175 Ball Head.



G1275 Ball Head.



G1275M Ball Head.



G1276 Ball Head.



G1375 Ball Head.



G1376 Ball Head.



G1575 Ball Head.



G1576 Ball Head.

Ref	Model	<u>B</u>	-	max	•	<b>Ø</b>		0
G075	Ball Head 0	1/4	13/8 Ø	31/4	+90°/-10°	10°/10°	360°	0
G1175	Ball Head 1	1/2	13/4 Ø	61/2	+90°/-5°	+5°/-5°	270°	1
G1275	Ball Head 2	13/4	13/4 x 21/2	11	+90°/-10°	360°	360°	2
G1275M	Ball Head 2	11/4	13/4 x 21/2	11	+90°/-10°	360°	360°	2
G1276	Ball Head 2	13/4	1½ x 2	11	+90°/-10°	360°	360°	2
G1375	Ball Head 3	21/4	2 <sup>3</sup> /8 x 2 <sup>3</sup> /4	131/4	+90°/-10°	360°	360°	3
G1376	Ball Head 3	25/8	21/4 x 21/4	131/4	+90°/-10°	360°	360°	3
G1575	Ball Head 4/5	3	23/8 x 23/4	22	+90°/-10°	360°	360°	4/5
G1576	Ball Head 4/5	31/2	21/4 x 21/4	22	+90°/-10°	360°	360°	4/5

## Rationnelle Three-way Heads



Ref	Model			max	*	<b>\$</b>	$\bigcirc$	0
G1171	Three Way Head	13/4	1½x 13/4	51/2	+90°/-60°	90°/50°	360°	0/1
G1172	Three Way Head	13/4	1½ x 35	51/2	$+90^{\circ}$ /- $60^{\circ}$	90°/50°	360°	0/1
G1371	Three Way Head	31/4	2 <sup>3</sup> / <sub>4</sub> x 2	13	$+90^{\circ}$ /- $60^{\circ}$	90°/50°	360°	3
G1372	Three Way Head	31/4	2 x 2	13	+90°/-60°	90°/50°	360°	2/3
G1571	Three Way Head	33/4	3 <sup>3</sup> / <sub>4</sub> x 2 <sup>3</sup> / <sub>4</sub>	175/8	$+90^{\circ}$ /- $60^{\circ}$	90°/50°	360°	4/5
G1572	Three Way Head	37/8	2 x 2	175/8	+90°/-60°	90°/50°	360°	4/5

### Rationnelle Low Profile Heads

The low profile heads provide solid support and flexibility for heavier large format cameras. The distance from the top of the tripod to the camera platform is reduced to ensure that the center of gravity of the camera is kept over the middle of the tripod to avoid the possibility of overbalancing.

All models can pan smoothly through  $360^\circ$  and provide a vertical tilt of  $+90^\circ$  and  $-20^\circ$ . Side to side movement is  $60^\circ$  to the left and  $90^\circ$  to the right, allowing the photographer to direct the camera at virtually any angle without compromising on stability.

The G1570 has a larger platform and two mounting screws and is especially suitable for monorail cameras. It is supplied with  $^{1}/_{4}$ " and  $^{3}/_{8}$ " camera mounting screws.



G1270 Low Profile Head.

G1570 Low Profile Head

Model	lbs		max		<b>Ø</b>	$\bigcirc$	$\odot$
Low Profile Head	11/2	4 <sup>3</sup> / <sub>4</sub> x 2 <sup>3</sup> / <sub>4</sub>	10	+90°/-20°	90°/60°	360°	1/2
Low Profile Head	23/8	4 <sup>3</sup> / <sub>4</sub> x 2 <sup>3</sup> / <sub>4</sub>	131/4	+90°/-20°	90°/60°	360°	3
Low Profile Head	31/2	6 x 3 <sup>3</sup> / <sub>8</sub>	22	+90°/-20°	90°/60°	360°	4/5
	Low Profile Head  Low Profile Head	Low Profile Head 11/2 Low Profile Head 23/8	Low Profile Head 11/2 43/4 x 23/4 Low Profile Head 23/8 43/4 x 23/4	Low Profile Head 11/2 43/4 x 23/4 10 Low Profile Head 23/8 43/4 x 23/4 131/4	Low Profile Head 1½ 43/4 x 23/4 10 +90°/-20° Low Profile Head 23/8 43/4 x 23/4 131/4 +90°/-20°	Low Profile Head 11/2 43/4 x 23/4 10 +90°/-20° 90°/60° Low Profile Head 23/8 43/4 x 23/4 131/4 +90°/-20° 90°/60°	Low Profile Head 11/2 43/4 x 23/4 10 +90°/-20° 90°/60° 360° Low Profile Head 23/8 43/4 x 23/4 131/4 +90°/-20° 90°/60° 360°

### **GITZO HEAD & TRIPOD** 35 SLR CAMERA **MEDIUM FORMAT** LARGE FORMAT 300mm Camera w. 300mm or Shorter Telephoto Lens comm Camera w 200mm or Shorter Telephoto Lene 35mm Camera with Wide Angle, Standard, 100mm or Shorter Lens **GUIDE** 35mm Camera 300mm or 6 x 6, 6 x 5 Can with Standard 6 x 6, 6 x 5 Camer with 200mm Lens \_onger 6 x 6,6 x 7 Camer with 300mm Lens 5 x 7 View Camera 8 x 10 View Camera 1 x 5 View Camera x 7 Camera with tandard Lens x 5 Field Camera A guide to the various applications of 200mm the complete Gitzo range of tripods, heads and ball heads, designed to facilitate a variety of specialist requirements **SERIES** REFERENCE G1171 G1172 HEADS G1370 G1371 G1372 • G1570 G1571 G1572 G075 BALLHEADS G1175 G1275 G1275M G1276 G1375 G1376 G101 G106 G112 G118 • G201 G212 G218 G220 G224 G226 G228 G1222 TRIPODS G1228 G1338 G1348 G1548 • G341 G342 G345 G346 G347 • • • • • • • : : • G500 G501 G502 G504 G505 G506 G507 G508 G509 G515



G1285 Quick Release Adaptor: for Series 1 & 2 Heads.



G1385 Quick Release Adaptor: for Series 3 & 5 Heads.



G583 Offset Bracket Ideal for cameras with handgrip or large lenses. Or where attaching Polaroid® backs impinges on the camera platform.



Quick Release Long



Quick Release Standard



### G065 Monitor Platform

A 330mm x 400mm platform which can be fitted to any Gitzo tripod. Safely supports supplementary equipment such as monitors, mixers, tape recorders.



### **Canvas Aprons** G088S Small G088L Large

Strapped to the tripod leas this immensely tough apron allows you to vary the tripod viewpoint without misplacing accessories.



### G1586 Location Shoe (Set of 3)

All weather shoe's for in snow, mud, sand etc.



### G1539 & G1584 **Double Platforms**

G1539 enables cameras (or 2 heads) to be mountedat 133/4" centers - to a tripod column. With G1584 you can couple two cameras to one tripod, 81/4" centers. Suitable for 35mm or 6 x 4.5 cameras.



tripods provide stability



### G087 Strap

Single size adjustable strap for all tripods, incorporating an anti-slip shoulder pad.

### **Quick Release Adaptors**

Designed to covert fixed plate heads to quick release ensuring, simple, positive and above all, rapid camera fixing. Two sizes are offered, for 1 - 2 Series (small/medium cameras) and for 3 - 5 Series heads (medium/large format cameras). These adaptors can also be mounted on other manufactures heads or tripods. Optional long plates are available.

### **Quick Release Plates**

Ref	Description	For
G1174/14	1/4" Long Plate	1276, 1172, 1285
G1174/38	3/8" Long Plate	1276, 1172, 1285
G1374/14	1/4" Long Plate	1372, 1576, G1572, 1385, 1376
G1374/38	3/8" Long Plate	1372, 1576, G1572, 1385, 1376
G1173/14	1/4" Standard Plate	1276, 1172, 1285
G1173/38	3/8" Standard Plate	1276, 1172, 1285
G1373/14	1/4" Standard Plate	1372, 1576, 1385, 1376
G1373/38	3/8" Standard Plate	1372, 1576, 1385, 1376
D1372.43	1/4" Camera Screw	1172, 1276, 1372, 1376, 1576,
		G1572, 1285, 1385
D1373.43	3/8" Camera Screw	1172, 1276, 1372, 1376, 1576,
		G1572, 1285, 1385
The second second		

### **Screw Types**

3/8" and 1/4" camera fixing screws.



Ref No	Thread.	Suitable for heads	
055-25	1/4"	G055	



172.37 172.38 172.39

Ref No	Thread.	Suitable for heads
D172-37	3/8"	G170, G172, G272, G275, G372, G375, G376, G472
D172-38	1/4"	G170, G172, G272, G275, G372, G375, G376, G472
D172-39		G170, G172, G272, G275, G372, G375, G376, G472







050.26 050.25 150.27

050.27

Ref No Thread.	Suitable for heads
<b>D050-26</b> 3/8"	G1171, G1270, G1275, G1275M, G1370, G1371, G1570, G1575, G1571
D050-25 1/4"	G1171, G1270, G1275, G1275M, G1370, G1371, G1570, G1575, G1571
D150-27	G1370, G1371, G1375, G1570, G1575, G1571
D050-27	G1270, Monopodes G558, G1565, G1171, G1275, G1275M

# Professional Video

Gitzo has set the standard for still and cine/video camera supports for over 80 years and has drawn on this experience to develop a professional range of cine/video tripods, fluid heads, microphone boom poles and accessories.

With a full range of high tensile aluminum and lightweight carbon fiber tripods, along with the new Gitzo G1380 Fluid head series, Gitzo now offers the perfect support solution for the professional cine/videographer.

Gitzo's unique tripod design eliminates the need to carry several tripods. The Gitzo Performance tripods offer the flexibility of optional leg angle spread for low or high shooting situations.

Utilizing the finest high strength metal alloys along with the legendary Gitzo twist lock design, strength and torsional rigidity is optimized. Each tripod has been designed to withstand a specified maximum weight even the when the tripod legs have been spread open, eliminating the need for midlevel or floor spreaders. Gitzo tripods are compact, lightweight and durable. Gitzo cine/video tripods accommodates most video fluid heads with optional 75mm or 100mm bowl interface.

The Gitzo G1380 series fluid heads complete the perfect support solution for the ENG cine/videographer. Incorporating smooth finger tip drag control with repeatable accuracy the Gitzo G1380 Fluid head along with a Gitzo cine/video tripod are the perfect match for the professional's needs!





### G1380 Fluid Head

The G1380 is the perfect video support for the new generation of lightweight ENG professional cameras.

The head features separate pan and tilt, variable drag control to produce smooth and repeatable movements without sticking or jerky stops and starts. A separate pan and tilt lock is included for added security.

The sliding camera platform provides convenient camera balancing with a quick engage and disengage quick release system. A safety release lock prevents the camera sliding off.

The G1380 has a factory installed counter-balance spring available in two versions which accomodates today's ENG cameras. (Counter-balance springs are available in 15.4 and 22 pound capacities).

Mounted on the G1338 Mountaineer carbon fiber tripod, the G1380 series fluid head completes the perfect support solution for today and tommorrow's professional videographers needs.

### Key Features Pavload Options

,		
G1380/7		$\pm$ 15.4lbs
G1380/10		$\pm$ 22lbs
Tilt		± 85°
Tilt Drag		Variable
Independent Ti	It Lock	~
Pan		360°
Pan Drag		Variable
Independent Pa	an Lock	~
Head Bowl		75mm
Levelling Bubb	le	~
Pan Bar		1
Optional Pan B	ar	~
Sliding Quick	Sun	plied with:
Release Plate		8 1 x <sup>1</sup> /4"

G1380 Fluid Head Kits

5lbs

Head Weight

Kits comprises: G1380 Fluid head, G1338 Mountaineer tripod, GE3VP Gitzo tripod bag and G087 Strap.

G1380/7KIT 10.4lbs G1380/10KIT 10.4lbs



(1) Tilt and (2) Pan (LF)Lubricated Friction Drag Controls.(3) Spirit Level.




(1) Pan lock.(2) Tilt lock.(3) Quick Release Safety Button.



(1) Sliding Quick Release Plate.(2) Quick Release Lock.

### Counterbalance Graph



The counterbalance graph indicates the ideal combination of center of gravity height to weight. The head will provide perfect balance throughout this tilt range.

18

# G1423 100mm Interface Bowl. Weight: 11/3/bs.



G1422 75mm Interface Bowl. Weight: 1/4 lbs.



G1424 100mm Interface Bowl. Weight: 1/2 lbs.



G321 Levelling Base. Weight: 13/8/bs.



Microphone Boom Pole.



### G391 Dolly max load 33lbs -3" wheels. G392 Dolly max load 44lbs -

5" wheels. Both Dollies offer immediate maneuverability, can be folded away and have individual wheel locks. Both units have camera fixings for floor level shooting.



### Microphone Boom Poles

Two models of the Gitzo Microphone Boom Poles are available - a three section pole, G556, and a four section pole, G557. These can be used in conjunction with the optional Microphone Holder G11510 which holds a range of sizes of microphones.

Ref	lbs	<b>小</b>	$\Lambda$	0
G556	1	79	313/4	3/4, 5/8, 7/16
G557	13/4	1033/4	303/4	7/8, 3/4, 5/8, 7/16

### Microphone Holder

	Outside Dia.	Inside Usable Dia.	Length	Height	
G11510	27/16	11/3	27/8.	35/8,	

### **Bowl Adaptors**

G1422 and G1424 interface bowls convert Series 3 - 4 - 5 tripods without center columns to take video heads from all manufactures with 75mm and 100mm ball.

G1423 adaptor enables video heads with 100mm ball to be fixed mounted on tripods with 3/8" screw head fixing.

### **Levelling Bases**

Gitzo levelling bases have a 15° adjustment and all are fitted with a spirit level. Efficient locking is ensured by a toggle lever.

Ref	Model		max		
G321	Levelling Base	13/8	22	340, 345	
G421	Levelling Base	11/4	33	410, 500, 515	

### Gitzo Photo/Video Tripod Bags



GE0 Standard Tripod Bag

These waterproof durable bags have been designed to carry all sizes of tripods and heads, and they are built to last. Practical and stylish, all the bags have zip fasteners for quick and easy access.

STANDARD BAG	PADDED BAG	TRIPOD SERIES	LENGTH INCHES	DIAMETER INCHES
GE0		0	212/3	4
GE1		1	27 1/2	4
	GE1P	1	27 1/2	4
GE2		2	33	4
	GE2P	2	33	4
GE3		3	37	6
	GE3P	3	37	6
	GE3PV	3	36	6
GE4		4	381/2	7 4/5
	GE4P	4	381/2	7 4/5
GE5		5	42	91/2
	GE5P	5	42	91/2

### PRODUCT INDEX

**TRIPODS** 

Ref	Model		W	小	ı İ	lbs	max	Page
MOUNT		R	60 <sup>7</sup> /8	121/2	201/2	3	131/2	4
G1228 G1338	Mountaineer Mountaineer	0	59	153/8	271/8	45/8	261/2	4
G1348	Mountaineer	Ō	653/4	153/8	24	45/8	261/2	5
G1349	Mountaineer	R	783/4	17	26	51/2	261/2	5
G1548	Mountaineer	0	581/4	15	231/4	63/8	391/2	5
G0011	Table Triped	R	185/8	65/8	81/2	3/4	61/2	6
	Table Tripod	н	189/8	69/8	81/2	9/4	01/2	0
VEEKEI 301	·Standard	R	481/2	16	171/4	2	51/2	6
3026	Compact Performance	R	541/2	113/4	15	21/4	51/2	6
SPORT	Ctandard	R	E 41/-	173/4	191/2	3	. 10	7
G101 G106	Standard Standard Tatalux	R	541/2 521/8	125/8	135/8	23/4	10	7
G120	Performance	R	581/4	113/8	205/8	31/4	10	7
G126	Performance Tatalux	R	583/4	12	15	3	10	7
G112 G118	Performance Geared 1 Short Column	G	561/2 511/8	113/4	21½ 215/8	33/4	10	7
REPORT	TER	5	W.					
3201	Standard	R	571/2	181/4	193/4	4	131/4	7
3220	Performance	R	581/4	123/4	211/4	41/4	131/4	7
G1222 G224	Monotripod Industrial Performance	R R	73 <sup>1</sup> / <sub>8</sub> 73 <sup>3</sup> / <sub>4</sub>	13½ 145/8	24 25	5 <sup>1</sup> / <sub>4</sub>	131/4	7
3226	Compact Performance	R	581/2	103/4	173/4	41/4	131/4	7
3228	Performance	G	64	12	181/2	41/2	131/4	7
3212 3218	Performance Geared 2 Short Column	G G	69 <sup>1</sup> / <sub>2</sub>	15 15	25½ 26	51/2 51/2	131/4	7
		<u> </u>	00-74	10	20	0 /2	10 /4	
STUDEX 3320	Performance	R	731/2	163/8	28	61/2	193/4	8
1322	Monotripod	R	721/4	143/8	241/4	63/4	193/4	8
3326	Compact Performance	R	711/4 69 <sup>7</sup> /8	131/4	221/4	71/4	193/4	8
3312 3328	Performance Compact	G G	69 <sup>7</sup> /8	17½ 13½	28 <sup>1</sup> / <sub>4</sub> 23 <sup>1</sup> / <sub>4</sub>	7 <sup>1</sup> / <sub>4</sub> 6 <sup>3</sup> / <sub>4</sub>	19 <sup>3</sup> / <sub>4</sub>	8
	PRO STUDEX							
3340	Performance	0	601/2	163/8	273/8	6	22	8
3341	Performance	R	753/4	181/2	291/2	7	22	8
G342 G345	Performance Compact Performance	G O	74 57 <sup>3</sup> / <sub>4</sub>	18½ 14½	29 <sup>1</sup> / <sub>2</sub> 22 <sup>1</sup> / <sub>2</sub>	8 <sup>1</sup> / <sub>4</sub>	22 22	8
3346	Compact Performance	R	721/4	163/4	241/4	61/2	22	8
3347	Compact Performance	G	711/8	163/4	241/4	73/4	22	8
PRO ST								
3410	Performance	0	641/8	193/8	291/2	81/2	26	9
3411 3412	Performance Performance	R G	781/2 75 <sup>7</sup> /8	211/2	311/4	93/4	22 26	9
3415	Compact Performance	0	451/2	13	191/4	63/4	26	9
G416	Compact Performance	R	59 <sup>7</sup> /8	143/4	21	8	22	9
G417	Compact Performance	G	571/4	143/4	21	93/4	26	9
TELE ST 3500	Fudex Performance	0	631/4	191/4	281/2	93/4	33	9
G501	Performance	R	761/2	211/2	303/4	103/4	22	9
G502	Performance	G	74	211/2	303/4	121/2	33	9
G504	Giant Performance	0	98	20	311/2	121/4	33	9
3508 3509	Giant Performance Giant Performance	R G	1111/ <sub>4</sub> 108 <sup>3</sup> / <sub>4</sub>	221/4	333/4	131/ <sub>4</sub> 151/ <sub>4</sub>	22 33	9
G505	Compact Performance	0	583/8	161/4	231/4	9	33	9
G506	Compact Performance	R	713/4	181/2	251/2	101/4	22	9
3507 3515	Compact Performance Performance Industrial	G 0	69 <sup>1</sup> / <sub>8</sub> 47 <sup>3</sup> / <sub>4</sub>	18½ 21¾	25½ 32½	12 81/2	33	9
			479/4	219/4	JZ 1/2	0.72	44	
	OPODS	0	Ī	Ŧ	F	bs	max	D
Ref 31560	Model  MonoTrek®	3/4	633/4	303/4		7/8	41/2	Page 10
31560	Sport	7/8	611/8	243/4		1/4	63/4	10
31563	Reporter	11/8	64	211/4	1	1/2	83/4	10
31563L	Reporter	11/8	801/4	223/8		1/2	83/4	10
31564 31564L	Studex Studex	11/4	621/2 781/2	21 <sup>5</sup> / <sub>8</sub> 22 <sup>3</sup> / <sub>8</sub>		<sup>3</sup> / <sub>4</sub>	171/2 171/2	10
G1565	Studex with brace	11/4	623/4	217/8		2	171/2	10
G566	Mini-Studex	11/4	531/4	141/2		1/2	11	10
G558 G1568	Gitzopod Mountaineer	11/4	60 <sup>1</sup> / <sub>4</sub>	26½ 215/8		1/4	11 8 <sup>3</sup> / <sub>4</sub>	10
		1 70	00 /4	2170			0 /4	10
CENT Ref	ER COLUMNS Model				lb	s	$\bigcirc$	Pag
EXTRA I	LOW							
	Sport	Ω	R R	-	1/.		2	11
	Contar column for C122	0	R		1/:		2	11
G1238	Center column for G122 Reporter				1/:		3	11
G1238 G235C G335C	Reporter Studex & Inter Pro Stude	ЭX	R			2		11
G1238 G235C G335C	Reporter	ex		-	1/	2		
91238 9235C 9335C 9435 STUDEX	Reporter Studex & Inter Pro Stude Pro Studex	ex	R				3	11
G1238 G235C G335C G435 STUDEX G315	Reporter Studex & Inter Pro Stude Pro Studex	ex	R R	-	1/:			11
G135C G1238 G235C G335C G435 STUDEX G315 G317 G336	Reporter Studex & Inter Pro Stude Pro Studex  Standard Compact Standard	ex	R R R R G	17 15 17 <sup>3</sup> /8	1/: 1 1 21:	/4	3 3 3	11 11
G1238 G235C G335C G435 STUDEX G315 G317 G336	Reporter Studex & Inter Pro Stude Pro Studex   Standard Compact	ex	R R R	17 15	1/:	/4	3	11
31238 3235C 3335C 3435 STUDEX 3315 3317 3336 3338 PRO ST	Reporter Studex & Inter Pro Stude Pro Studex   Standard Compact Standard Compact Compact Compact Compact Compact Compact Compact Compact		R R R G G	17 15 17 <sup>3</sup> / <sub>8</sub> 14	1/ 1 1 1 21 2	/4	3 3 3 3	11 11 11
31238 3235C 3335C 3435 STUDEX 3315 3317 3336 3338 PRO ST 3525	Reporter Studex & Inter Pro Stude Pro Studex  Standard Compact Standard Compact UDEX AND TELE STUD Standard		R R R G G	17 15 17 <sup>3</sup> / <sub>8</sub> 14	1/1 1 1 21 2	/4	3 3 3 3 4 + 5	11 11 11
31238 3235C 3335C 3435 STUDEX 3315 3317 3336 3338 PRO ST 3525 3524	Reporter Studex & Inter Pro Stude Pro Studex   Standard Compact Standard Compact Compact Compact Compact Compact Compact Compact Compact		R R R G G	17 15 17 <sup>3</sup> / <sub>8</sub> 14	1/ 1 1 1 21 2	/4	3 3 3 3 3 4+5 4+5 4+5	11 11 11
G1238 G235C G335C G435 STUDEX G315 G317 G336 G338 PRO ST G525 G524 G527 G526	Reporter Studex & Inter Pro Stude Pro Studex  Standard Compact Standard Compact Standard Compact UDEX AND TELE STUD Standard Standard Double Compact Standard		R R R G G	17 15 173/8 14 131/4 28 101/4 103/4	1/21/22 11/13/11/11	/4  2  4  4  2	3 3 3 3 4+5 4+5 4+5 4+5	11 11 11 11 11 11 11
G1238 G235C G335C G435 STUDEX G315 G317 G336 G338	Reporter Studex & Inter Pro Stude Pro Studex   Standard Compact Standard Compact UDEX AND TELE STUD Standard Standard Standard Compact Ompact Compact		R R R G G	17 15 17 <sup>3</sup> / <sub>8</sub> 14 13 <sup>1</sup> / <sub>4</sub> 28 10 <sup>1</sup> / <sub>4</sub>	1/21 21 21 11 13	/4 /2 /4 /2 /4	3 3 3 3 3 4+5 4+5 4+5	11 11 11 11 11 11

Ref	RAL ARMS Model	m	Ĩ		lbs	$\odot$	Page
G530	Sport	R	15	111/4	3/4	1	. 11
G531	Sport	G	143/4	101/8	1	17.	11
G532	Reporter	R	173/4	13	1	2	11
G533	Reporter	G	181/4	13	13/4	2	11
G534	Inter Pro Studex	R	181/8	131/2	1	3	11
G535	Inter Pro Studex	G	181/2	123/4	2	3	11

S	0		0	-				
Model	lbs		max		<b>Ø</b>	$\bigcirc$	$\odot$	Page
EADS								
Ball Head 0	1/4	13/8 Ø	31/4	+90°/-10°	10°/10°	360°	0	14
Ball Head 1	1/2	13/4 Ø	61/2	+90°/-5°	+5°/-5°	270°	1	14
Ball Head 2	13/4	13/4 x 21/2	11	+90°/-10°	360°	360°	2	14
Ball Head 2	11/4	13/4 x 21/2	11	+90°/-10°	360°	360°	2	14
Ball Head 2	13/4	11/2 x 2	11	+90°/-10°	360°	360°	2	14
Ball Head 3	21/4	23/8 x 23/4	131/4	+90°/-10°	360°	360°	3	14
Ball Head 3	25/8	21/4 x 21/4	131/4	+90°/-10°	360°	360°	3	14
Ball Head 4/5	3.	23/8 x 23/4	22	+90°/-10°	360°	360°	4/5	14
Ball Head 4/5	31/2	21/4 x 21/4	22	+90°/-10°	360° -	360°	4/5	14
NELLE THREE WAY	/ HEAD	S						
Three Way Head	13/4	11/2 x 13/4	51/2	+90°/-60°	90°/50°	360°	0/1	15
Three Way Head	13/4	11/2 x 35	51/2	+90/-60°	90°/50°	360°	0/1	15
Three Way Head	31/4	23/4 x 2	. 13	+90/-60°	90°/50°	360°	3	15
Three Way Head	31/4	2 x 2	13	+90/-60°	90°/50°	360°	2/3	15
Three Way Head	33/4	33/4 x 23/4	175/8	+90/-60°	90°/50°	360°	4/5	15
Three Way Head	37/8	2 x 2	175/8	+90/-60°	90°/50°	360°	4/5	15
NELLE LOW PROF	LE HE	ADS						
Low Profile Head	11/2	43/4 x 23/4	10	+90°/-20°	90°/60°	360°	1/2	16
Low Profile Head	23/8	43/4 x 23/4	131/4	+90°/-20°	90°/60°	360°	3	16
Low Profile Head	31/2	6 x 3 <sup>3</sup> / <sub>8</sub>	22	+90°/-20°	90°/60°	360°	4/5	16
IDEO HEADS								
<b>0</b> Fluid Video Head	5	31/2 x 13/4	22	+85°/-85°	+85°/-85°	360°	3/5	18
Fluid Video Head	5	31/2 x 13/4	15.4	+85°/-85°	+85°/-85°	360°	3/5	18
	Model EADS Ball Head 0 Ball Head 1 Ball Head 2 Ball Head 2 Ball Head 2 Ball Head 3 Ball Head 3 Ball Head 3 Ball Head 4/5 Ball Head 4/5 NELLE THREE WAY Three Way Head	Model  EADS  Ball Head 0 1/4  Ball Head 1 1/2  Ball Head 2 13/4  Ball Head 2 11/4  Ball Head 2 13/4  Ball Head 3 2/5  Ball Head 3 25/6  Ball Head 3 25/6  Ball Head 4/5 3.2  Ball Head 4/5 3.3  Ball Head 4/5 3.4  ELLE THREE WAY HEAD  Three Way Head 13/4  Three Way Head 31/4  Three Way Head 31/4  Three Way Head 31/4  Three Way Head 31/4  Three Way Head 31/6  Three Wa	Model  EADS  Ball Head 0	Model  EADS  Ball Head 0 1/4 13/6 Ø 31/4  Ball Head 1 1/2 13/4 Ø 61/2  Ball Head 2 13/4 13/4 × 21/2 11  Ball Head 2 11/4 13/4 × 21/2 11  Ball Head 2 13/4 11/2 × 2 11  Ball Head 2 13/4 11/2 × 2 11  Ball Head 3 21/4 23/6 × 23/4 131/4  Ball Head 3 21/4 23/6 × 23/4 131/4  Ball Head 3 25/6 21/4 × 21/4 131/4  Ball Head 4/5 3 23/6 × 23/4 22/4  Ball Head 4/5 3 1/2 × 21/4 22/4 22/4  Ball Head 4/5 3 1/2 × 23/6 × 23/4 22/4  Ball Head 4/5 3 1/2 × 23/6 × 23/4 22/4  Ball Head 4/5 3 1/4 2 1/4 × 21/4 22/4  Ball Head 4/5 3 2/4 × 21/4 22/4  Ball Head 4/5 3 2/4 × 21/4 22/4  Ball Head 4/5 3 2/4 × 21/4 22/4  Ball Head 4/5 3 1/2 × 13/4 51/2  Three Way Head 13/4 11/2 × 13/4 51/2  Three Way Head 31/4 2/4 × 2 13  Three Way Head 31/4 2 × 2 13  Three Way Head 33/4 33/4 × 23/4 175/6  Three Way Head 17/2 43/4 × 23/4 10  Low Profile Head 17/2 43/4 × 23/4 10  Low Profile Head 31/2 6 × 33/8 22  IDEO HEADS  Discription of the state o	Model   Mod	Model  EADS  Ball Head 0 1/4 13/8 Ø 31/4 +90°/-10° 10°/10°  Ball Head 1 1/2 13/4 Ø 61/2 +90°/-5° 1-5°/-5°  Ball Head 2 13/4 13/4 × 21/2 11 +90°/-10° 360°  Ball Head 2 13/4 13/4 × 21/2 11 +90°/-10° 360°  Ball Head 2 13/4 11/2 × 2 11 +90°/-10° 360°  Ball Head 3 21/4 23/8 × 23/4 131/4 +90°/-10° 360°  Ball Head 3 25/8 21/4 × 21/4 131/4 +90°/-10° 360°  Ball Head 3 25/8 21/4 × 21/4 22 +90°/-10° 360°  Ball Head 3 25/8 21/4 × 21/4 22 +90°/-10° 360°  Ball Head 4/5 3 23/8 × 23/4 22 +90°/-10° 360°  Ball Head 4/5 31/2 21/4 × 21/4 22 +90°/-10° 360°  Ball Head 4/5 3 51/2 21/4 × 21/4 22 +90°/-10° 360°  Ball Head 3 13/4 11/2 × 13/4 51/2 +90°/-60° 90°/50°  Three Way Head 13/4 11/2 × 35 51/2 +90′-60° 90°/50°  Three Way Head 31/4 22/4 × 2 13 +90/-60° 90°/50°  Three Way Head 33/4 23/4 × 2 13 +90/-60° 90°/50°  Three Way Head 33/4 33/4 × 22 13 +90/-60° 90°/50°  Three Way Head 37/8 2 × 2 175/8 +90/-60° 90°/50°  Three Way Head 31/2 43/8 × 23/4 175/8 +90/-60° 90°/50°  NELLE LOW PROFILE HEADS  Low Profile Head 11/2 43/8 × 23/4 10 +90°/-20° 90°/60°  Low Profile Head 31/2 43/8 × 23/4 10 +90°/-20° 90°/60°  Low Profile Head 31/2 43/8 × 23/4 13/4 +90°/-20° 90°/60°  Low Profile Head 31/2 43/8 × 23/4 13/4 +90°/-20° 90°/60°  Low Profile Head 31/2 43/8 × 23/4 13/4 +90°/-20° 90°/60°  Low Profile Head 31/2 43/8 × 23/4 13/4 +90°/-20° 90°/60°  Low Profile Head 51/2 43/8 × 23/4 13/4 +90°/-20° 90°/60°  Low Profile Head 51/2 43/8 × 23/4 13/4 +90°/-20° 90°/60°  Low Profile Head 51/2 43/8 × 23/4 13/4 +90°/-20° 90°/60°  Low Profile Head 51/2 43/8 × 23/4 13/4 +90°/-20° 90°/60°  Low Profile Head 51/2 43/8 × 23/4 13/4 +90°/-20° 90°/60°	Model	Model

FISHP Ref	OLES Model	(lbs	lack	$\Lambda$	0	Page
G556	Microphone Boom Pole	1	79	313/4	3/4, 5/8, 7/16	19
G557	Microphone Boom Pole	13/4	1033/4	303/4	7/8, 3/4, 5/8, 7/16	19
		Outside Dia.	Inside Usable Dia.	Length	Height	
G11510	Microphone holder	27/16	11/3	27/8,	35/8.	19

LEVEL Ref	LING BASES Model		lin max		Page
G321	Levelling Base	13/8	22	340, 345	19
G421	Levelling Base	11/4	33	410, 500, 515	19
G1422	Adaptor to 75mm Bowl	1/4	-	3 & 4	19
G1423	Adaptor to 100mm Bowl	11/3	33	-	19
G1424	Adaptor to 75mm Bowl	1/2	33	-	19

Ref	SSORIES Model	lbs	Page
GE.01-		to 12/8 -	-
GE.5	Tripod Bags	25/8	19
G391	Dolly	121/2	19
G392	Dolly	141/2	19
G1393	Tripod Spreader	11/2	17
G088S	Small Canvas Apron	1/4	17
G088L	Large Canvas Apron	3/8	17
G1586	Location Shoe	1/2	17
G1539	Double Platform	2	17
G1584	Double Platform	1	17

and the second	SSORIES	æ	D
Ref	Model	ius	Page
G1285	Quick Release Adapter		17
G1385	Quick Release Adapter	5/8	17
G583	Offset Bracket	1/4	17
G087	Strap	3/8	17
G065	Monitor Platform	21/2	17
G349	Circular Camera Plat.	3/8	11
G449	Circular Camera Plat.	1/4	11
G540	Right Angle Bracket	3/4	11
G541	Grad. R.A. Bracket	13/4	11

### KEY TO SYMBOLS

$\stackrel{\frown}{\bigcirc}$	Min Height
	Tripod Series
$\oslash$	Top Tube





$\overline{\mathbf{V}}$	Max Height
max	Max Load lbs
	Travel
////	Arm Type

Column Type : O=No column R=Rapid G=Geared

In the interest of further improving the Gitzo range, Gitzo reserve the right to change the specification within this catalog at any time.





Bogen Photo: (201) 818-9500

Fax: (201) 818-9177 Service Only: (201) 818-0060
565 E. Crescent Avenue, P.O. Box 506,
Ramsey, NJ 07446-0506